

		REVISIONS			
REV	ECO	DESCRIPTION	DATE	BY	APPR
A1		RELEASE NEW DRAWING	24/MAY/23	MILO	TOMMY



55.4±0.5 Ø42.3±0.5 M35 x 1.75 THREAD



NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL:

HOUSING: THERMOPLASTIC; BLACK

SEAL: SILICONE RUBBER

2. MODIFICATIONS: SMALL THREADED ADAPTER (STA); STANDARD DIA. WIRE SEAL;

- 3. SPECIFICATIONS:
 - 3.1 OPERATING TEMPERATURE: -55°C TO +125°C.
 - 3.2 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.3 INSULATION RESISTANCE: 1000 MEGOHM MIN @ 25°C.
 - 3.4 MOISTURE RESISTANCE:

IP68(IM OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION);

IP69K(MATED CONDITION)

- 3.5 MATING CYCLE DURABILITY: 100 CYCLES
- 3.6 RoHS COMPLIANT
- 4. MATING PART: AHDP02-24-23P*-XXX & AHDP04-24-23P*-XXX (* = SEAL TYPE, XXX = ALL MODIFICATIONS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

6 CONTACT SIZE AND WIRE RANGE:

CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL	CURRENT
SIZE	O.D.	O.D.	WIRE RANGE	RATING
16	2.54 mm (.100 in)	3.40 mm (.134 in)	14-20 AWG (2.0-0.5mm²)	

7. CONDUIT ADAPTER ACCEPTS BACKSHELL (AHDPBS-24L015-005) CABLE Ø14.5 ~ Ø18.0.



SMALL THREADED ADAPTER -GREEN

	AHDP06-2	24-23SN-STA			REF:HDP26-24-23SN-L015				
QUANTITY PART NUMBER			DESCRIPTION				ITEM		
MATERI				ERI	ALS	3 LI	ST		
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC ±0.30 Fractions ±1/64		SIGN	SIGNATURES DATE		1 manhanal				
		DRAWN:	MILO.DONG	24/MAY/23	Amphenol				
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED: SL	JLLEN.ZHANG	25/MAY/23		Sin	e Systems - www.ampher	ol-sine.com	
3) Note reference	3) Note reference = X				44724 Morley Drive				
MATERIAL SPECIFICA			TOMMY.XIE	26/MAY/23	Clinton Township, MI 48036				
=		CUSTOMER:			1	23	POS,PLUG,SOCKE	ET,24SZ,	
WEIGH	WEIGHT: 65.5g		THIS DRAWING IS SUPPLIED FOR		NORMAL SEAL,STA,DURAMATE AHDP)P
PROCESS SPECIFICATIONS:		INFORMATION ONLY. DESIGN FEATURES, SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE MIPLIED, ALL JOINENSIONS ARE SUBJECT TO NORMAL MANUFACTURING VARIATIONS.		В	C-	AHDP06-24-2	3SN-STA	A1	
NEXT ASS'Y:				SCALE: N	ONE	DURAMATE	SHEET 1 C	F 1	

A Series™ - Contact Size 16 Options (Works with: AT, ATV, AHD-9, ARC, DuraMate and PanelMate Series)

	Machined Contacts, Sockets & Pins						
Part Number	Description	Size	AWG	Туре			
AT60-215-1631	Male Contact - Pin, Gold-plated	16	14	Machined			
AT62-209-1631	Female Contact - Socket, Gold-plated	16	14	Machined			
AT60-215-16141	Male Contact - Pin, Nickel-plated	16	14	Machined			
AT62-209-16141	Female Contact - Socket, Nickel-plated	16	14	Machined			
AT60-202-1631	Male Contact - Pin, Gold-plated	16	16-20	Machined			
AT62-201-1631	Female Contact - Socket, Gold-plated	16	16-20	Machined			
AT60-202-16141	Male Contact - Pin, Nickel-plated	16	16-20	Machined			
AT62-201-16141	Female Contact - Socket, Nickel-plated	16	16-20	Machined			
AT60-202-1631-22	Male Contact - Pin, Gold-plated	16	22-24	Machined			
AT62-201-1631-22	Female Contact - Socket, Gold-plated	16	22-24	Machined			
AT60-202-16141-22	Male Contact - Pin, Nickel-plated	16	22-24	Machined			
AT62-201-16141-22	Female Contact - Socket, Nickel-plated	16	22-24	Machined			

Tooling - Machined Contacts				
Part Number	Description			
AUTK-16	Hand Crimp Tool, Size 16			
AUTK-100	Universal Heavy Duty Contact Crimping Tool Kit, Size 12/16/20			
CA-5D12	Universal Hand Crimp Tool, Size 12/16/20			
CA-5E12	Pneumatic Crimp Tool, Size 12/16/20			

Contact Removal Tools (For both Machined or Stamped & Formed Contacts)				
Part Number	Description			
ATRT-100	Contact and Wedgelock Extraction Tool			
AT11-310-1605	Contact Removal Tool, Plastic, Size 16			

Sealing Plugs (For both Machined or Stamped & Formed Contacts)					
Part Number	Description				
A114017	Sealing Plug, Size 16, White				
A114017-SR	Sealing Plug, Size 16, SR01 Series, Black				
AT13-217-1605	Locking Sealing Plug, Size 16, Grey				
AT13-217-1605-SR	Locking Sealing Plug, Size 16, SR01 Series, Red				

Stamped & Formed Contacts, Sockets & Pins						
Description	Size	AWG	Туре			
Male Contact - Pin, Nickel-plated	16	14-18	Stamped & Formed			
Female Contact - Socket, Nickel-plated	16	14-18	Stamped & Formed			
Male Contact - Pin, Gold-plated	16	14-18	Stamped & Formed			
Female Contact - Socket, Gold-plated	16	14-18	Stamped & Formed			
Male Contact - Pin, Nickel-plated	16	16-18	Stamped & Formed			
Female Contact - Socket, Nickel-plated	16	16-18	Stamped & Formed			
Male Contact - Pin, Gold-plated	16	16-18	Stamped & Formed			
Female Contact - Socket, Gold-plated	16	16-18	Stamped & Formed			
Male Contact - Pin, Nickel-plated	16	16-20	Stamped & Formed			
Female Contact - Socket, Nickel-plated	16	16-20	Stamped & Formed			
Male Contact - Pin, Gold-plated	16	16-20	Stamped & Formed			
Female Contact - Socket, Gold-plated	16	16-20	Stamped & Formed			
Male Contact - Pin, Tin-plated	16	16-20	Stamped & Formed			
Female Contact - Socket, Tin-plated	16	16-20	Stamped & Formed			
Male Contact - Pin, Nickel-plated	16	20-22	Stamped & Formed			
Female Contact - Socket, Nickel-plated	16	20-22	Stamped & Formed			
Male Contact - Pin, Gold-plated	16	20-22	Stamped & Formed			
Female Contact - Socket, Gold-plated	16	20-22	Stamped & Formed			
	Description Male Contact - Pin, Nickel-plated Female Contact - Socket, Nickel-plated Male Contact - Pin, Gold-plated Female Contact - Socket, Gold-plated Male Contact - Pin, Nickel-plated Male Contact - Pin, Nickel-plated Male Contact - Socket, Nickel-plated Male Contact - Socket, Nickel-plated Male Contact - Socket, Gold-plated Female Contact - Socket, Gold-plated Male Contact - Pin, Nickel-plated Female Contact - Socket, Nickel-plated Male Contact - Pin, Gold-plated Female Contact - Socket, Gold-plated Male Contact - Pin, Tin-plated Female Contact - Pin, Tin-plated Male Contact - Pin, Nickel-plated Male Contact - Pin, Gold-plated	DescriptionSizeMale Contact - Pin, Nickel-plated16Female Contact - Socket, Nickel-plated16Male Contact - Pin, Gold-plated16Female Contact - Socket, Gold-plated16Male Contact - Pin, Nickel-plated16Female Contact - Pin, Nickel-plated16Male Contact - Pin, Gold-plated16Female Contact - Pin, Gold-plated16Male Contact - Pin, Mickel-plated16Female Contact - Socket, Gold-plated16Female Contact - Pin, Nickel-plated16Male Contact - Pin, Gold-plated16Female Contact - Socket, Gold-plated16Male Contact - Pin, Tin-plated16Female Contact - Pin, Tin-plated16Male Contact - Pin, Nickel-plated16Male Contact - Pin, Nickel-plated16Female Contact - Socket, Nickel-plated16Male Contact - Pin, Nickel-plated16Male Contact - Pin, Nickel-plated16Male Contact - Pin, Gold-plated16	DescriptionSizeAWGMale Contact - Pin, Nickel-plated1614-18Female Contact - Socket, Nickel-plated1614-18Male Contact - Pin, Gold-plated1614-18Female Contact - Socket, Gold-plated1614-18Male Contact - Pin, Nickel-plated1616-18Female Contact - Socket, Nickel-plated1616-18Male Contact - Pin, Gold-plated1616-18Female Contact - Socket, Gold-plated1616-18Male Contact - Pin, Nickel-plated1616-20Female Contact - Socket, Nickel-plated1616-20Male Contact - Pin, Gold-plated1616-20Female Contact - Socket, Gold-plated1616-20Male Contact - Pin, Tin-plated1616-20Female Contact - Pin, Tin-plated1616-20Male Contact - Pin, Nickel-plated1616-20Male Contact - Socket, Tin-plated1616-20Male Contact - Pin, Nickel-plated1620-22Female Contact - Socket, Nickel-plated1620-22Male Contact - Pin, Gold-plated1620-22			

Tooling - Stamped & Formed Contacts				
MFX-3950	Crimp Die - Size 16, 18-20AWG			
MFX-3953	Crimp Die - Size 16, 16-18AWG			
MFX-3975	Crimp Die - Size 16, 14-16AWG			
MFX-3990	Crimp Die - Size 16, 20-22AWG			
ATT-16-00	Hand Crimp Tool - Size 16, 14-16AWG			
ATT-16-01	Hand Crimp Tool - Size 16, 18-20AWG			
ATT-1612-03	Hand Crimp Tool - Size 16, 20-22AWG			