



4800 Staticide® Ultra II Floor Finish

Designed for Unique Industrial Surfaces

Whether revitalizing old ESD tiles or protecting a new epoxy floor, Staticide® Ultra II Floor Finish helps safeguard your costly investment of specialized flooring. Advanced acrylic polymer allows superior adhesion and static control for out-of-warranty ESD floors and other special surfaces. This distinctive anti-static blend is compatible with problematic plasticizers found in conductive and dissipative tiles and epoxy and is also suitable to use on concrete.

The urethane-enhanced formula's high abrasion resistance and durability leave floors static dissipative, glossy, and protected for 12-18 months. It does not yellow or flake and is tough to scuff. Staticide® Ultra II Floor Finish is ideal for any environment where static control is required and ESD flooring is installed, including sensitive device manufacturing areas.

Staticide® Ultra II Floor Finish is UL-listed for slip resistance and is free of formaldehyde, phthalates, alkalis, acids, and ammonia.

Directions:

Clean floor and apply two thin coats of floor finish with a dedicated rayon mop. Wait one hour between coats. Consult application procedure for details and precise instructions.

Maintenance:

Sweep or damp mop daily to remove dirt. Periodically clean with a 1:1 dilution of water and floor finish. Apply a thin topcoat of floor finish every 4 – 6 weeks. For heavy cleaning, use the #4100 Staticide® Restorer Cleaner. Consult maintenance procedure for details and precise instructions.

Product# 4800-1: 4 gallons per case

Product# 4800-5: 5-gallon pail

Product# 4800-2: 54-gallon drum



Ideal for the following applications:

- Electronic manufacturing facilities
- Medical facilities
- Cleanrooms

FEATURES:

- ❖ **Coverage: 1,500 – 2,000 square feet per gallon**
- ❖ **Non-toxic; biodegradable**
- ❖ **Non-flammable**
- ❖ **Strip cycle: 12 – 18 months**
- ❖ **Low V.O.C.**
- ❖ **Water-based acrylic**
- ❖ **RoHS compliant**
- ❖ **10e7 – 10e9 ohms per ANSI/ESD STM 7.1 and ESD TR53**