

RG174 LSFH, 50 Ohm, 1 GHz, 85°C, ø2.8 mm, LSFH jacket

G_02262

Properties

- Custom version of RG_174
- Low smoke



Construction			
Component	Material	Detail	Diameter
Centre conductor	Copper	Strand-07, 96 %, RAL 9005 - bk	0.49 mm - 0.1 mm
Dielectric	PE (Polyethylene)		1.5 mm
Outer conductor	Copper	Braid, 96%	2 mm
Jacket	LSFH (modified polyethylene)	RAL 9005 - bk	2.8 mm +/- 0.1 mm

Electrical data	
Impedance	50 Ω +/-2Ω
Operating frequency	≤ 1 GHz
Capacitance	101 pF/m
Velocity of signal propagation	66 %
Signal delay	5.03 ns/m
Screening effectiveness	38 dB at frequency 0.001 GHz ... 1GHz
Insulation resistance	100000000 MΩ*m
Operating Voltage (at sea level)	≤ 1.5 kVrms
Test voltage (50 Hz/1 min)	≤ 3 kVrms
Noise level	10 mV

Mechanical data	
Weight	approx. 13.3 g/m
Static bending radius	≥ 15 mm
Repeated bending radius	28 mm

Environmental data	
Operation temperature	-40 °C ... 85 °C
Installation temperature	-20 °C ... 60°C
Flame propagation standard	IEC 60332-1

RG174 LSFH, 50 Ohm, 1 GHz, 85°C, Ø2.8 mm, LSFH jacket

G_02262

Environmental data			
Fire characteristics		free of halogenes, acc. standard IEC 60754	
Suitable connectors			
Cable group		U2	
Ordering information			
Item number	Item description	Available as assembly only	
22510862	G_02262	No	
Power Matrix			
Calculation: typical Attenuation [formula: (a*f^0.5 + b*f)] and maximum Power CW [formula: (p/f^0.5)]			
a coefficient typical =	0.867	b coefficient typical =	0.1289
fmax =	1.0	P at 1 GHz =	38.0
Frequency	Nom. attenuation	Nom. attenuation	CW power
GHz	(dB/m)	(dB/ft)	(W)
	sea level 25°C ambient temperature	sea level 25°C ambient temperature	sea level 40°C ambient temperature
0.10	0.287	0.087	120
0.20	0.414	0.126	85
0.30	0.514	0.157	69
0.40	0.600	0.183	60
0.60	0.749	0.228	49
0.80	0.879	0.268	42
1.00	0.996	0.304	38

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P1082 / Date of publication: 26.02.2024 / uncontrolled copy