

product type designation

IWLAN RCoax Cable 2 GHz

IWLAN RCoax cable PE 1/2 2.4 GHz long distance -40 °C/+85 °C ext. temperature range. Sold by the meter minimum order quantity 20 m delivery unit: max. 500 m.



suitability for operation

For example, suspended monorails, cranes, stacker cranes. Line is water-repellent, resistant to microbes, and extremely resistant to many cleaning agents and disinfectants (such as iodophors, peroxyacetic acids (1% solution), and quaternary ammonium cations). Cleaning with high-pressure cleaner up to 50 kg.

radio frequencies

operating frequency

- for WLAN in 2.4 GHz frequency band

2.4 ... 2.485 GHz

electrical data

impedance

50 Ω

attenuation factor per length

- at 2.4 GHz / with cable mounted 10 mm above concrete / at 20 °C
- at 2.4 GHz / with cable mounted 15 mm above aluminum rail / at 20 °C

0.15 dB/m

0.17 dB/m

coupling attenuation

- at 2.4 GHz / at 20 °C
- note

35 dB

c(50) for distance of 10 cm between antenna and cable

capacity per length

76 pF/m

DC resistance per length

- of inner conductor / at 20 °C
- of coaxial line conductor / at 20 °C

1.48 Ω/km

2.8 Ω/km

relative speed

88 %

mechanical data

outer diameter

- of inner conductor
- of dielectric
- of cable sheath

4.8 mm

12.4 mm

15.5 mm

thickness / of cable sheath

1.3 mm

material

- of inner conductor
- of dielectric
- of coaxial line conductor
- of cable sheath

Copper clad aluminum

Polyethylene foam

Overlapping copper foil with the slot groups bonded to cable jacket

Halogen-free polyolefine

color / of cable sheath

pastel turquoise

bending radius

- with single bend / minimum permissible

200 mm

number of bending cycles

1

tensile load / maximum

1100 N

weight per length

0.232 kg/m

mounting distance

• recommended	0.5 m
ambient conditions	
ambient temperature	
• during operation	-40 ... +85 °C
• during storage	-70 ... +85 °C
• during installation	-25 ... +60 °C
product feature / resistant to UV radiation	Yes
standards, specifications, approvals	
standard	
• for fire behavior	
— corrosive gas emission	IEC 60754-2
— smoke emission	IEC 60332-1 and IEC 60332-3 Cat. C
— flame resistance	IEC 61034
certificate of suitability	
• UL approval	Yes
wireless approval	Current national approvals can be found on the Internet under www.siemens.com/funkzulassungen
reference code / according to IEC 81346-2:2019	TFB
further information / internet links	
internet link	
• to web page: selection aid TIA Selection Tool	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAX-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
last modified:	4/28/2023 