


LTR	DESCRIPTION	DATE	BY
A	RELEASE	11/17/22	WW

I. CONSTRUCTION



Center	.070"	Solid Bare Copper
Dielectric	.190"	Foam Polyethylene
Inner Shield	.196"	Al-Polyester-Al-Adhesive Tape
Outer Braid	.225"	Tinned Copper Braids(90%k)
Inner Jacket	.300"	Black LSZH FR Polyethylene

Print Legend: "LMR[®]-300-LSZH ■ COAXIAL ■ CABLE ■  ■ TIMES ■ MICROWAVE ■ SYSTEMS ■ PH+1(203) ■ 949-8400 ■ DD/MM/YY ■ C ■ ■ ■ × × × × × M"

II. ENVIRONMENTAL and MECHANICAL PROPERTIES

Weight:	61 pounds per 1000 feet
Operating Temperature:	-40°C to +85°C
Minimum Bend Radius:	2.25 inches


III. ELECTRICAL PROPERTIES

Impedance:	50 ohms
Capacitance:	24.1 pF per foot
Velocity:	84%

Attenuation(+25°C) (Typical)	Frequency	dB/100ft
	150 MHz:	2.4
	450 MHz:	4.2
	900 MHz:	6.1
	2000 MHz:	9.2
	2500 MHz:	10.4
	5800 MHz:	16.5

IV. NOTES

- 1) All tests performed in accordance with MIL-DTL-17 (current issue).
- 2) All materials are ROHS and REACH compliant.

This document contains Times Microwave Systems proprietary information. It shall not be duplicated, used or disclosed in whole or in part to third parties without written authorization from Times Microwave Systems. This data is EAR controlled IAW 15 CFR Part 730-774. MI	Approvals			 TIMES MICROWAVE SYSTEMS Wallingford, CT 06492 (203) 949-8400; (203) 949-8423.Fax www.timesmicrowave.com
	Drawn	WW	11/17/22	
	Checked	MT	11/17/22	
	Approved	CW	11/17/22	LMR-300-LSZH
	This Technical Specification is for Reference only			CAGE CODE: 68999
Unless specified all dimensions are in inches.			Rev. (A)	Sheet: 1 of 1