

COAXIAL ADAPTER, 7/16 Quick-mate - N, 50 Ohm, jack / jack (female / female)

31_716-N-Q50-1/1-3_N

Properties

- Wide range of different configurations
- Most common interfaces available
- Accurate transitions
- Effective and reliable interconnection solutions
- Appropriate materials



Product configuration		
Interface type	Gender	Standard
7/16 Quick-mate	jack (female)	HUBER+SUHNER Quick-mate
N	jack (female)	IEC 61169-16_MIL-STD-348A/304_CECC 22210

Interface and material data		
7/16 Quick-mate		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer conductor	Bronze	SUCOPRO Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
N		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Body		SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Electrical data	
Impedance	50 Ω
Interface frequency	7.5 GHz

Mechanical data	
Weight	0.0642 kg
Mating cycles	500

Environmental data	
Operation temperature	-65 °C ... 165°C

COAXIAL ADAPTER, 7/16 Quick-mate - N, 50 Ohm, jack / jack (female / female)
31_716-N-Q50-1/1-3_N

Ordering Information Table		
Item number	Item description	Packaging type
23008294	31_716-N-Q50-1/1-3_NE	Single

Additional Information	
Remarks	Durability of QUICK MATE interface: 1000 matings

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2421 / Date of publication: 26.11.2023 / uncontrolled copy