

COAXIAL ADAPTER, MMCX - SMA, 50 Ohm, jack / jack (female / female)

31_MMCX-SMA-50-1/111_O

Properties

- Wide range of different configurations
- Most common interfaces available
- Accurate transitions
- Effective and reliable interconnection solutions
- Appropriate materials



Product configuration		
Interface type	Gender	Standard
MMCX	jack (female)	HUBER+SUHNER-MMCX
SMA	jack (female)	IEC 60169-15_MIL-STD-348A/310_CEEC 22110

Interface and material data		
MMCX		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Brass	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	
SMA		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Body		Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	

Electrical data	
Impedance	50 Ω
Interface frequency	6 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 2.5 GHz	26 dB	1.1
2.5 GHz ... 6 GHz	21 dB	1.18

COAXIAL ADAPTER, MMCX - SMA, 50 Ohm, jack / jack (female / female)

31_MMCX-SMA-50-1/111_O

Mechanical data	
Weight	0.0043 kg
Mating cycles	500

Environmental data	
Operation temperature	-55 °C ... 125°C

Ordering Information Table		
Item number	Item description	Packaging type
22645961	31_MMCX-SMA-50-1/111_OE	Single

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2402 / Date of publication: 26.11.2023 / uncontrolled copy