


COAXIAL ADAPTER, SMA - SMB, 50 Ohm, jack / jack (female / female)

31_SMA-SMB-50-1/111_U

Properties

- Wide range of different configurations
- Most common interfaces available
- Accurate transitions
- Effective and reliable interconnection solutions
- Appropriate materials



Product configuration

Interface type	Gender	Standard
SMA	jack (female)	IEC 60169-15_MIL-STD-348A/310_CECC 22110
SMB	jack (female)	IEC 60169-10_MIL-STD-348A/311_CECC 22130

Interface and material data

SMA		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer conductor	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Body	Brass	Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	
SMB		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Body		Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	

Electrical data

Impedance	50 Ω
Interface frequency	4 GHz

Mechanical data

Weight	0.0045 kg
Mating cycles	500

Environmental data

Operation temperature	-65 °C ... 165 °C
-----------------------	-------------------

COAXIAL ADAPTER, SMA - SMB, 50 Ohm, jack / jack (female / female)

31_SMA-SMB-50-1/111_U

Ordering Information Table		
Item number	Item description	Packaging type
22641728	31_SMA-SMB-50-1/111_U	Single

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2367 / Date of publication: 26.11.2023 / uncontrolled copy