

COAXIAL ADAPTER, PC 1, 50 Ohm, plug / plug (male / male)

32_PC1-50-0-1/11-_UE

Properties

- Precision interfaces
- Excellent electrical performance
- Premium base materials and platings



Product configuration		
Interface type	Gender	Standard
PC 1	plug (male)	IEEE 287:2007
PC 1	plug (male)	IEEE 287:2007

Interface and material data		
PC 1		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer conductor	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Body	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Insulator	PEEK (Polyether-etherketone)	
Coupling nut	Stainless Steel	Passivated (Plating)
PC 1		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Body		Gold Plating (without Nickel underplating)
Insulator	PEEK (Polyether-etherketone)	
Coupling nut	Stainless Steel	Passivated (Plating)

Electrical data	
Impedance	50 Ω
Interface frequency	110 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 50 GHz	20 dB	1.222
50 GHz ... 75 GHz	17.5 dB	1.308

COAXIAL ADAPTER, PC 1, 50 Ohm, plug / plug (male / male)
32_PC1-50-0-1/11-_UE

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
75 GHz ... 110 GHz	16 dB	1.377
Mechanical data		
Weight	0.004 kg	
Mating cycles	100	
Environmental data		
Operation temperature	15 °C ... 30 °C	
Ordering Information Table		
Item number	Item description	Packaging type
85031743	32_PC1-50-0-1/11-_UE	Single

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2294 / Date of publication: 12.04.2024 / uncontrolled copy