

COAXIAL ADAPTER, 1.0/2.3 - SMA, 50 Ohm, plug / jack (male / female)

33_1023-SMA-C50-1/111_N

Properties

- Wide range of different configurations
- Most common interfaces available
- Accurate transitions
- Effective and reliable interconnection solutions
- Appropriate materials



Product configuration		
Interface type	Gender	Standard
1.0/2.3 C50	plug (male)	DIN 41626/2
SMA	jack (female)	IEC 60169-15_MIL-STD-348A/310_CECC 22110

Interface and material data		
1.0/2.3 C50		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body	Brass	Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	
SMA		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body		Gold Plating (Nickel underplated)
Insulator	PFA / PTFE	

Electrical data	
Impedance	50 Ω
Interface frequency	4 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 4 GHz	27 dB	1.09

COAXIAL ADAPTER, 1.0/2.3 - SMA, 50 Ohm, plug / jack (male / female)
33_1023-SMA-C50-1/111_N

Mechanical data	
Weight	0.0029 kg
Mating cycles	500

Environmental data	
Operation temperature	-55 °C ... 125°C

Ordering Information Table		
Item number	Item description	Packaging type
22652963	33_1023-SMA-C50-1/111_NE	Single

Additional Information	
Remarks	Insertion loss: < 0.1 dB up to 4 GHz

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2275 / Date of publication: 26.11.2023 / uncontrolled copy