

COAXIAL ADAPTER, MCX - BNC, 50 Ohm, plug / jack (male / female)

33_MCX-BNC-50-1/1--_U

Properties

- Wide range of different configurations
- Most common interfaces available
- Accurate transitions
- Effective and reliable interconnection solutions
- Appropriate materials



Product configuration		
Interface type	Gender	Standard
MCX	plug (male)	IEC 60169-36_CEECC 22220
BNC	jack (female)	IEC 61169-8_MIL-STD-348A/301_CEECC 22120

Interface and material data		
MCX		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer conductor	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Body	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Insulator	PFA / PTFE	
BNC		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Body		SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Electrical data	
Impedance	50 Ω
Interface frequency	4 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 1 GHz	34 dB	1.04
1 GHz ... 3 GHz	17.9 dB	1.29
3 GHz ... 4 GHz	16 dB	1.377

COAXIAL ADAPTER, MCX - BNC, 50 Ohm, plug / jack (male / female)
33_MCX-BNC-50-1/1--_U

Mechanical data		
Weight	0.0061 kg	
Mating cycles	500	
Environmental data		
Operation temperature	-55 °C ... 155°C	
Ordering Information Table		
Item number	Item description	Packaging type
22543585	33_MCX-BNC-50-1/1--_UE	Single

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2231 / Date of publication: 26.11.2023 / uncontrolled copy