

COAXIAL ADAPTER, PC 3.5 - 4.3-10, 50 Ohm, plug / jack (male / female)

33_PC35-4310-50-1/1-9_N

Properties

- Precision interfaces
- Excellent electrical performance
- Premium base materials and platings



Product configuration		
Interface type	Gender	Standard
PC 3.5	plug (male)	IEC 60169-23
4.3-10	jack (female)	IEC 61169-54

Interface and material data		
PC 3.5		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Outer conductor	Bronze / Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Coupling nut	Stainless Steel	
4.3-10		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	SUCOPRO Plating
Body		SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Electrical data	
Interface frequency	12 GHz

Electrical Data (frequency related)		
Frequency range	Return loss	VSWR
0 GHz ... 4 GHz	36 dB	1.032
4 GHz ... 6 GHz	32 dB	1.052

COAXIAL ADAPTER, PC 3.5 - 4.3-10, 50 Ohm, plug / jack (male / female)

33_PC35-4310-50-1/1-9_N

Mechanical data	
Weight	0.028652 kg
Mating cycles	500

Environmental data	
Operation temperature	-55 °C ... 90°C

Ordering Information Table		
Item number	Item description	Packaging type
85017256	33_PC35-4310-50-1/1-9_NE	Single

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2181 / Date of publication: 26.11.2023 / uncontrolled copy