

COAXIAL ADAPTER, BNC - QLA, X Ohm, Bulkhead, jack / jack (female / female)

34_BNC-QLA-01-1/1--_U

Properties

- Wide range of different configurations
- Most common interfaces available
- Accurate transitions
- Effective and reliable interconnection solutions
- Appropriate materials



Product configuration		
Interface type	Gender	Standard
BNC	jack (female)	IEC 61169-8_MIL-STD-348A/301_CEECC 22120
QLA-01	jack (female)	NIM-CAMAC-Standard CD/N549

Interface and material data		
BNC		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer		SUCOPLATE (R) Plating
QLA-01		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (without Nickel underplating)
Body		SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Fastening nut	Brass	
Washer	Bronze	

Electrical data	
Interface frequency	1.4 GHz

Mechanical data	
Weight	0.0092 kg
Mating cycles	500

COAXIAL ADAPTER, BNC - QLA, X Ohm, Bulkhead, jack / jack (female / female)
34_BNC-QLA-01-1/1--_U

Environmental data	
Operation temperature	-55 °C ... 150 °C

Ordering Information Table		
Item number	Item description	Packaging type
22640971	34_BNC-QLA-01-1/1--_UE	Single

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2118 / Date of publication: 12.04.2024 / uncontrolled copy