

COAXIAL ADAPTER, MMCX, 50 Ohm, Bulkhead, jack / jack (female / female)

34_MMCX-50-0-1/11_O

Properties

- Wide range of different configurations
- Most common interfaces available
- Accurate transitions
- Effective and reliable interconnection solutions
- Appropriate materials



CE UK
CA

Product configuration

| | | |
|----------------|---------------|-------------------|
| Interface type | Gender | Standard |
| MMCX | jack (female) | HUBER+SUHNER-MMCX |
| MMCX | jack (female) | HUBER+SUHNER-MMCX |

Interface and material data

| MMCX | Material | Plating |
|--------------------|------------------------|--|
| Piece parts | | |
| Centre contact | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Outer conductor | Brass | Gold Plating (without Nickel underplating) |
| Body | Brass | Gold Plating (without Nickel underplating) |
| Insulator | PFA / PTFE | |
| Fastening nut | Brass | Gold Plating (without Nickel underplating) |
| Washer | Brass | Gold Plating (without Nickel underplating) |
| MMCX | | |
| Piece parts | | |
| Centre contact | Copper Beryllium Alloy | Gold Plating (Nickel underplated) |
| Body | | Gold Plating (without Nickel underplating) |
| Insulator | PFA / PTFE | |
| Fastening nut | Brass | |
| Washer | Brass | Gold Plating (without Nickel underplating) |

Electrical data

| | |
|---------------------|-------|
| Impedance | 50 Ω |
| Interface frequency | 6 GHz |

Electrical Data (frequency related)

| Frequency range | Return loss | VSWR |
|-------------------|-------------|------|
| 0 GHz ... 1.5 GHz | 30 dB | 1.06 |

COAXIAL ADAPTER, MMCX, 50 Ohm, Bulkhead, jack / jack (female / female)
 34_MMCX-50-0-1/111_O

Electrical Data (frequency related)

| Frequency range | Return loss | VSWR |
|-------------------|-------------|------|
| 1.5 GHz ... 6 GHz | 20 dB | 1.22 |

Mechanical data

| | |
|---------------|-----------|
| Weight | 0.0008 kg |
| Mating cycles | 500 |

Environmental data

| | |
|-----------------------|------------------|
| Operation temperature | -55 °C ... 155°C |
|-----------------------|------------------|

Ordering Information Table

| Item number | Item description | Packaging type |
|-------------|-----------------------|----------------|
| 22650516 | 34_MMCX-50-0-1/111_OE | Single |

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
 DOCUMENT PIM-P2109 / Date of publication: 26.11.2023 / uncontrolled copy