

COAXIAL ADAPTER, BNC - N, 50 Ohm, Panel, jack / jack (female / female), flange mount

37_BNC-50-0-1/133_N

Properties

- Wide range of different configurations
- Most common interfaces available
- Accurate transitions
- Effective and reliable interconnection solutions
- Appropriate materials



Product configuration

Interface type	Gender	Standard
BNC	jack (female)	IEC 61169-8_MIL-STD-348A/301_CEEC 22120
BNC	jack (female)	IEC 61169-8_MIL-STD-348A/301_CEEC 22120

Interface and material data

BNC		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
BNC		
Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Body		SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Electrical data

Impedance	50 Ω
Interface frequency	4 GHz

Mechanical data

Weight	0.0134 kg
Mating cycles	500

Environmental data

Operation temperature	-65 °C ... 165 °C
-----------------------	-------------------

COAXIAL ADAPTER, BNC - N, 50 Ohm, Panel, jack / jack (female / female), flange mount

37_BNC-50-0-1/133_N

Ordering Information Table		
Item number	Item description	Packaging type
22540635	37_BNC-50-0-1/133_NE	Single

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P1933 / Date of publication: 26.11.2023 / uncontrolled copy