



C Female to C Female Bulkhead Adapter

RF Adapters Technical Data Sheet

PE9186

Configuration

- C Female Connector 1
- C Female Connector 2
- 50 Ohms

- Straight Body Geometry
- Bulkhead Mount Method

Features

- C Interface compliant with MIL-STD-348
- Silver Plated Contact
- Contact Plating per QQ-S-365

Applications

- General Purpose Test
- Rack Mounted Equipment

Description

Pasternack's PE9186 type C female to type C female bulkhead adapter is part of our full line of RF components available for same-day shipping. Our type C to type C adapter has a female to female gender configuration. This RF type C to type C bulkhead adapter allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Pasternack also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Mechanical Specifications

Size

Length	1.48 in [37.59 mm]
Width	1 in [25.4 mm]
Weight	0.116 lbs [52.62 g]

Description	Connector 1	Connector 2
Type	C Female	C Female
Polarity	Standard	Standard
Interface Specification	MIL-STD-348	MIL-STD-348

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [C Female to C Female Bulkhead Adapter PE9186](#)



C Female to C Female Bulkhead Adapter

RF Adapters Technical Data Sheet

PE9186

Material Specifications

Description	Material	Connector 1		Connector 2	
		Plating	Material	Plating	Material
Type	C Female		C Female		
Contact		Silver QQ-S-365		Silver QQ-S-365	
Insulation	PTFE		PTFE		
Outer Conductor	Brass	Nickel QQ-N-290	Brass	Nickel QQ-N-290	
Coupling Nut			Brass	Nickel QQ-N-290	

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:


C Female to C Female Bulkhead Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [C Female to C Female Bulkhead Adapter PE9186](#)

URL: <https://www.pasternack.com/c-female-c-female-straight-adapter-pe9186-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE9186 CAD Drawing
C Female to C Female Bulkhead Adapter



PE PASTERNACK®

Pasternack Enterprises, Inc.

P.O. Box 16759 | Irvine | CA | 92623

Phone: (949) 261-1920 | Fax: (949) 261-7451

Website: www.pasternack.com | E-Mail: sales@pasternack.com

PE9186

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

REV. A	FSCM NO.	53919	CAD FILE	060112	SCALE	N/A	SIZE	A	2233
--------	----------	-------	----------	--------	-------	-----	------	---	------