



75 Ohm SMB Plug to 50 Ohm BNC Female Adapter

RF Adapters Technical Data Sheet

PE9232

Configuration

- SMB Plug Connector 1
- BNC Female Connector 2
- 75 Ohms, 50 Ohms
- Straight Body Geometry

Features

- Gold Plated Beryllium Copper Contact
- 30 μ-in min Gold Contact Plating

Applications

- Allows Connection Between Series
- General Purpose Test

Description

Pasternack's PE9232 75 ohm SMB plug to 50 ohm BNC female adapter is part of our full line of RF components available for same-day shipping. Our SMB to BNC adapter has a plug to female gender configuration.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Pasternack also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Mechanical Specifications

Size

Length	1.267 in [32.18 mm]
Width	0.453 in [11.51 mm]
Weight	0.034 lbs [15.42 g]

Description	Connector 1	Connector 2
Type	SMB Plug	BNC Female
Polarity	Standard	Standard

Material Specifications

Description	Connector 1		Connector 2	
	Material	Plating	Material	Plating
Type	SMB Plug		BNC Female	
Contact	Beryllium Copper	Gold 30 μ-in minimum	Beryllium Copper	Gold 30 μ-in minimum
Insulation	PTFE		PTFE	
Outer Conductor			Brass	Nickel 100 μ-in minimum

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm SMB Plug to 50 Ohm BNC Female Adapter PE9232](#)



75 Ohm SMB Plug to 50 Ohm BNC Female Adapter

RF Adapters Technical Data Sheet

PE9232

Body	Brass	Nickel 100 μ-in minimum
Coupling Nut	Brass	Nickel 100 μ-in minimum

Compliance Certifications (see [product page](#) for current document)

75 Ohm SMB Plug to 50 Ohm BNC Female Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [75 Ohm SMB Plug to 50 Ohm BNC Female Adapter PE9232](#)

URL: <https://www.pasternack.com/smb-plug-bnc-female-straight-adapter-pe9232-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE9232 CAD Drawing

75 Ohm SMB Plug to 50 Ohm BNC Female Adapter



STANDARD TOLERANCES
 .X ±0.2
 .XX ±0.1
 .XXX ±0.05

*STANDARD TOLERANCES APPLY ONLY TO DIMENSIONS IN INCHES

NOTES:
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE
PE9232

(PE) PASTERNAK®
 THE ENGINEER'S RF SOURCE
 Pasternack Enterprises, Inc.
 P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | **Fax:** (949) 261-7451
Website: www.pasternack.com | **E-Mail:** sales@pasternack.com

FSCM NO. 53919

CAD FILE 022416 SCALE N/A SIZE A 3045