

N Male to SMC Plug Adapter



PE9318

TECHNICAL DATA SHEET

| N Male to SMC Plug Adapter | |
|---|---|
| Configuration Connector 1 Impedance 1 Connector 2 Impedance 2 Adapter Design Body Style | N Male 50 Ohms SMC Plug 50 Ohms Standard Straight |
| Mechanical Specifications | |
| Temperature Operating Range,deg C | -65 to +165 |
| Size Length, in [mm] Width/Dia., in [mm] | 1.23 [31.24] 0.8 [20.32] |
| Connector 1 Type Inner Conductor Material and Plating Inner Conductor Plating Specification Coupling Nut Material and Plating Body Material and Plating Dielectric Type Connector 2 Type Inner Conductor Material and Plating Inner Conductor Plating Specification Coupling Nut Material and Plating Hex Size, in. Torque, in-lbs [Nm] Body Material and Plating | N Male Gold MIL-G-45204 Brass, Nickel Brass, Nickel Teflon SMC Plug Gold MIL-G-45204 Brass, Nickel 1/4 3 [0.34] Brass, Nickel |
| Dielectric Type Compliance Certifications (visit www.Pasternack.com f | Teflon for current document) |
| RoHS Compliant | Yes |
| Plotted and Other Data Notes: | Values at 25 °C, sea level |
| URL: http://www.pasternack.com/n-male-smc-plug-straight-adapter-pe9318-p.aspx | |

N Male to SMC Plug Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com

PE9318 CAD Drawing

N Male to SMC Plug Adapter

