

## MMCX Jack to MCX Jack Adapter



## **TECHNICAL DATA SHEET**

PE9526

## **MMCX Jack to MCX Jack Adapter**

Co	nfia	uration

Connector 1 MMCX Jack
Impedance 1 50 Ohms
Connector 2 MCX Jack
Impedance 2 50 Ohms
Adapter Design Standard
Body Style Straight

## **Mechanical Specifications**

**Temperature** 

Operating Range,deg C -65 to +165

Size

Length, in [mm] 0.53 [13.46] Width/Dia., in [mm] 0.188 [4.78]

#### **Connector 1**

Type MMCX Jack
Inner Conductor Material and Plating Gold
Inner Conductor Plating Specification MIL-G-45204
Body Material and Plating Brass, Nickel
Dielectric Type Teflon

#### Connector 2

Type MCX Jack
Inner Conductor Material and Plating Gold
Inner Conductor Plating Specification MIL-G-45204
Body Material and Plating Brass, Nickel
Dielectric Type Teflon

## Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

## **Plotted and Other Data**

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/mmcx-jack-mcx-jack-straight-adapter-pe9526-p.aspx

MMCX Jack to MCX Jack Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com

# PE9526 CAD Drawing MMCX Jack to MCX Jack Adapter

