



7-16 DIN Male to 2.2-5 Female Adapter, Low PIM

RF Adapters Technical Data Sheet

PE9799

Configuration

- 7/16 DIN Male Connector 1
- 2.2-5 Female Connector 2
- 50 Ohm
- Low PIM Design
- Straight Body Geometry

Features

- Max VSWR of 1.25:1 up to 8 GHz
- Typical PIM levels of -160 dBc
- VSWR of 1.25:1 max up to 8 GHz
- PIM levels better than -160 dBc
- Low Coupling Torque
- Corrosion Resistant Tri-Metal finish

Applications

- Allows Connection Between Series
- General Purpose Test
- Low PIM Applications
- Enables Between Series Connections
- General Purpose Test
- Low PIM Applications
- Mobile Communications Systems
- Base Stations
- Distributed Antenna Systems
- Small Cells
- Feeder Cables

Description

Pasternack's PE9799 7/16 DIN male to 2.2-5 female adapter is part of our full line of RF components available for same-day shipping. Our 7/16 DIN to 2.2-5 adapter has a male to female gender configuration in a low PIM design. PE9799 7/16 DIN male to 2.2-5 female adapter operates to 8 GHz. The Pasternack RF adapter provides excellent VSWR of 1.25:1 maximum and passive intermodulation of -160 dBc typical.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Pasternack also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		8	GHz
VSWR			1.25:1	
Passive Intermodulation		-160		dBc
Dielectric Withstanding Voltage (AC)			750	Vrms

Mechanical Specifications

Size	
Length	0.09 in [2.29 mm]
Width	1.38 in [35.05 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [7-16 DIN Male to 2.2-5 Female Adapter, Low PIM PE9799](#)



7-16 DIN Male to 2.2-5 Female Adapter, Low PIM

RF Adapters Technical Data Sheet

PE9799

Weight 0.21 lbs [95.25 g]

Description	Connector 1	Connector 2
Type	7/16 DIN Male	2.2-5 Female
Polarity	Standard	Standard

Material Specifications

Description	Connector 1		Connector 2	
	Material	Plating	Material	Plating
Type	7/16 DIN Male		2.2-5 Female	
Contact	Beryllium Copper	Silver		
Insulation	PTFE		PTFE	
Outer Conductor			Beryllium Copper	Silver
Body	Brass	Tri-Metal	Brass	Tri-Metal
Coupling Nut	Brass	Tri-Metal	Brass	Tri-Metal

Environmental Specifications

Temperature

Operating Range -40 to +155 °C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [7-16 DIN Male to 2.2-5 Female Adapter, Low PIM PE9799](#)



7-16 DIN Male to 2.2-5 Female Adapter, Low PIM

RF Adapters Technical Data Sheet

PE9799

7-16 DIN Male to 2.2-5 Female Adapter, Low PIM from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [7-16 DIN Male to 2.2-5 Female Adapter, Low PIM PE9799](https://www.pasternack.com/7-16-din-male-2.2-5-female-straight-adapter-pe9799-p.aspx)


URL: <https://www.pasternack.com/7-16-din-male-2.2-5-female-straight-adapter-pe9799-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE9799 CAD Drawing

7-16 DIN Male to 2.2-5 Female Adapter, Low PIM

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	7/6/2021	A. GANWANI



THIRD-ANGLE PROJECTION

THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF PASTERNAK CORPORATION ALL RIGHTS RESERVED.

SHEET 1 OF 1

SCALE N/A

REV A

PE PASTERNAK
an INFINITE brand

Pasternack Enterprises, Inc.
P.O. Box 16759, Irvine, CA 92623.
Phone: 1.949.261.1920 | 1.866.727.8376
Fax: 1.949.261.7451
Website: www.pasternack.com
E-mail: sales@pasternack.com

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS

TOLERANCES:

X	± .2	[5.08]	FRACTIONS
.XX	± .02	[.51]	± 1/32
.XXX	± .005	[.13]	ANGLES ± 1°

CABLE LENGTH (L) TOLERANCES:

L ≤ 12 [305]	± .1 [25]	/ -0
12 [305] < L ≤ 60 [1524]	± .2 [51]	/ -0
60 [1524] < L ≤ 120 [3048]	± .4 [102]	/ -0
120 [3048] < L ≤ 300 [7620]	± .6 [152]	/ -0
300 [7620] < L	± 5%	/ -0


ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.

SIZE A

CAGE CODE 53919

DRAWN BY K.DANG

ITEM NO. PE9799



THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.