



SMPS Male Full Detent (FD) to 1.85mm
Male Adapter, 67 GHz, 50 Ohm

RF Adapters Technical Data Sheet

PE9992

Configuration

- Full Detent SMPS Male Connector 1
- 1.85mm Male Connector 2
- 50 Ohm
- Straight Body Geometry

Features

- 50 μ m minimum contact plating
- Gold Plated Beryllium Copper Contact

Applications

- Allows Connection Between Series
- General Purpose Test

Description

Pasternack's PE9992 full detent SMPS male to 1.85mm male adapter is part of our full line of RF components available for same-day shipping. Our SMPS to 1.85mm adapter has a male to male gender configuration built of durable stainless steel. PE9992 SMPS male to 1.85mm male adapter operates to 67 GHz.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Pasternack also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		67	GHz
Impedance		50 Ohm		
Insertion Loss			0.7	dB

Mechanical Specifications

Size	
Length	0.66 in [16.79 mm]
Width	0.35 in [8.99 mm]
Height	0.35 in [8.99 mm]
Weight	0.01 lbs [3.18 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMPS Male Full Detent \(FD\) to 1.85mm Male Adapter, 67 GHz, 50 Ohm PE9992](#)



SMPS Male Full Detent (FD) to 1.85mm
Male Adapter, 67 GHz, 50 Ohm

RF Adapters Technical Data Sheet

PE9992

Description	Connector 1	Connector 2
Type	SMPS Male	1.85mm Male
Polarity	Standard	Standard
Mating Cycles, Min*		500

Material Specifications

Description	Connector 1		Connector 2	
	Material	Plating	Material	Plating
Type	Full Detent SMPS Male		1.85mm Male	
Contact	Beryllium Copper	Gold 50 µin minimum	Beryllium Copper	Gold 50 µin minimum
Insulation	PEI		PEI	
Outer Conductor	Passivated Stainless Steel		Passivated Stainless Steel	
Body	Passivated Stainless Steel		Passivated Stainless Steel	

Environmental Specifications

Temperature

Operating Range -55 to -165 °C

Humidity

MIL-STD-202, Method 106, Less Step 7B

Shock

MIL-STD-202, Method 213, Condition I

Vibration

MIL-STD-202, Method 204, Condition D

Thermal Shock


MIL-STD-202, Method 107, Condition B

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMPS Male Full Detent \(FD\) to 1.85mm Male Adapter, 67 GHz, 50 Ohm PE9992](#)



SMPS Male Full Detent (FD) to 1.85mm
Male Adapter, 67 GHz, 50 Ohm

RF Adapters Technical Data Sheet

PE9992

SMPS Male Full Detent (FD) to 1.85mm Male Adapter, 67 GHz, 50 Ohm from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [SMPS Male Full Detent \(FD\) to 1.85mm Male Adapter, 67 GHz, 50 Ohm PE9992](https://www.pasternack.com/full-detent-smps-male-to-1.85mm-male-adapter-pe9992-p.aspx)

URL: <https://www.pasternack.com/full-detent-smps-male-to-1.85mm-male-adapter-pe9992-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE9992 CAD Drawing

SMPS Male Full Detent (FD) to 1.85mm Male Adapter, 67 GHz, 50 Ohm

