

TC-SPP375-716F-LP DATA SHEET

7/16 DIN Female Low PIM Connector Solder Attachment for SPP-375-LLPL, SPO-375, SPF-375 Cable

Times Microwave Systems Connector Specification

7/16 DIN female connector with solder/solder attachment for Times' SPP-375-LLPL, SPO-375 and SPF-375, part number TC-SPP375-716F-LP, from Times Microwave offered by Fairview Microwave is in-stock and ships same day. This 7/16 DIN female connector operates up to a maximum frequency of 6 GHz and offers excellent VSWR of 1.25:1.

Times Microwave's 7/16 DIN female connector TC-SPP375-716F-LP datasheet specifications and outline drawing are shown in this PDF below. Our extensive offering of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. From providing an I/O for a board design to creating a custom cable assembly configuration, Fairview Microwave has a connector solution to meet your needs. Fairview Microwave also has the expertise to build your custom cable assemblies for you and ship them same-day.

Electrical Specifications

Description	Min	Тур	Max	Units
Frequency Range	DC		6	GHz
VSWR			1.25:1	
Insertion Loss			0.25	dB
Operating Voltage (DC)			1,500	Vdc
Insulation Resistance	10,000			MOhms

Electrical Specification Notes:

Insertion Loss is 0.1*sqrt(FGHz)

Mechanical Specifications

Size

Length Width/Dia. 1.5 in [38.1 mm] 1.14 in [28.96 mm]

Material Specifications

Description	Material	Plating	
Contact	Phosphor Bronze	Silver 200 µin	
Insulation	PTFE		
Body	Brass	Tri-Metal 80 µin	

Environmental Specifications

Temperature

Operating Range Shock Vibration -55 to +85 deg C US MIL-STD 202G US MIL-STD 202G



Configuration:

- 7/16 DIN Female Connector
- 50 Ohms
- Straight Body Geometry
- SPP-375-LLPL, SPO-375, SPF-375 Interface Type
- Solder/Solder Attachment
- Low PIM Design

Features:

- Operating Frequency of 6 GHz Max.
- Excellent VSWR of 1.25:1
- Silver Plated Phosphor Bronze Contact
- · 200 µin contact plating

Applications:

- General Purpose Test
- Wireless Communications
- Custom Cable Assemblies
- Low PIM Applications
- Distributed Antenna Systems (DAS)

Fairview Microwave 301 Leora Ln., Suite 100 Lewisville, TX 75056 Tel: 1-800-715-4396 / (972) 649-6678 Fax: (972) 649-6689 www.fairviewmicrowave.com sales@fairviewmicrowave.com





Thermal Shock

US MIL-STD 202G

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

7/16 DIN Female Low PIM Connector Solder Attachment for SPP-375-LLPL, SPO-375, SPF-375 Cable from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: 7/16 DIN Female Low PIM Connector Solder Attachment for SPP-375-LLPL, SPO-375, SPF-375 Cable TC-SPP375-716F-LP

URL: https://www.fairviewmicrowave.com/7-16-din-female-spp-375-llpl-spo-375-spf-375-connector-tc-spp375-716f-lp-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.

301 Leora Ln., Suite 100, Lewisville, TX 75056 | Tel: 1-800-715-4396 / (972) 649-6678 / Fax: (972) 649-6689



TC-SPP375-716F-LP DATA SHEET

