

COAXIAL CONNECTOR, BNT, 50 Ohm, Straight bulkhead receptacle, jack (female)

22_BNT-50-0-1/103_N

Properties

Useful for frequently coupled and uncoupled connections



Product configuration

Interface type	Gender	Standard
BNT	jack	HUBER+SUHNER-BNT

Interface and material data

Piece parts	Material	Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer conductor	Bronze	Silver Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Fastening nut	Brass	SUCOPLATE (R) Plating
Washer	Bronze	SUCOPLATE (R) Plating

Electrical data

Impedance	50 Ω
Interface frequency	3 GHz

Mechanical data

Weight	0.0073 kg
Mating cycles	500
Flange type	round flange / dia. 12.5
Tab style	solder end

Environmental data

Operation temperature	-50 °C ... 125°C
-----------------------	------------------

COAXIAL CONNECTOR, BNT, 50 Ohm, Straight bulkhead receptacle, jack (female)
22_BNT-50-0-1/103_N

Ordering Information Table		
Item number	Item description	Packaging type
22541069	22_BNT-50-0-1/103_NE	Single

Additional Information	
Remarks	Triaxial Connector Front mount chassis connector

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/ EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2813 / Date of publication: 26.11.2023 / uncontrolled copy