


COAXIAL CONNECTOR, QMA, 50 Ohm, Straight bulkhead receptacle, jack (female)

22_QMA-50-0-4/133_N

Properties

- Excellent electrical performance
- High packing density
- Applicable in frequencies up to 18 GHz
- Easy to mate - No torque or tooling required
- Return loss optimized DC to 6 GHz



Product configuration

Interface type	Gender	Standard
QMA	jack	QMA QLF compliant

Interface and material data

Piece parts	Material	Plating
Centre contact	Copper Beryllium / Bronze	SUCOPRO Plating
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	

Electrical data

Impedance	50 Ω
Interface frequency	6 GHz

Mechanical data

Weight	0.0022 kg
Mating cycles	100
Flange type	hexagonal flange / hex 8
Tab style	Standard

Environmental data

Operation temperature	-40 °C ... 85°C
-----------------------	-----------------

Ordering Information Table

Item number	Item description	Packaging type
23022628	22_QMA-50-0-4/133_NH	Bulk 100 pcs

COAXIAL CONNECTOR, QMA, 50 Ohm, Straight bulkhead receptacle, jack (female)
22_QMA-50-0-4/133_N

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P2790 / Date of publication: 26.11.2023 / uncontrolled copy