

SMA Female Connector Solder Attachment for RG188-DS, RG316-DS



RF Connectors Technical Data Sheet

PE4417

Configuration

- SMA Female Connector
- •50 Ohms
- Straight Body Geometry

- RG188-DS, RG316-DS Interface Type
- Solder/Solder Attachment

Features

- Max. Operating Frequency 18 GHz
- Good VSWR of 1.5:1

• Gold Plated Beryllium Copper Contact

Applications

General Purpose Test

Custom Cable Assemblies

Description

Pasternack's PE4417 SMA female connector with solder/solder attachment for RG188-DS and RG316-DS is part of our full line of RF components available for same-day shipping. Our SMA female connector operates up to a maximum frequency of 18 GHz and offers good VSWR of 1.5:1.

Our SMA female connector PE4417 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
VSWR			1.5:1	
Operating Voltage (AC)			250	Vrms
Dielectric Withstanding Voltage (AC)			750	Vrms

Mechanical Specifications

Size

 Length
 0.603 in [15.32 mm]

 Width/Dia.
 0.312 in [7.92 mm]

 Weight
 0.008 lbs [3.63 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Connector Solder Attachment for RG188-DS, RG316-DS PE4417

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (868) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com . Techsupport@Pasternack.com



SMA Female Connector Solder Attachment for RG188-DS, RG316-DS



RF Connectors
Technical Data Sheet

PE4417

Material Specifications

Description	Material	Plating	
Contact	Beryllium Copper	Gold	
Insulation	PTFE		
Outer Conductor	Brass	Nickel	
Body	Brass	Gold	

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

SMA Female Connector Solder Attachment for RG188-DS, RG316-DS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Connector Solder Attachment for RG188-DS, RG316-DS PE4417

URL: https://www.pasternack.com/sma-female-standard-rg188-ds-rg316-ds-connector-pe4417-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (868) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451

Sales@Pasternack.com . Techsupport@Pasternack.com

PE4417 CAD Drawing

SMA Female Connector Solder Attachment for RG188-DS, RG316-DS

