



SSMA Female Connector Crimp/Solder Attachment For RG178, RG196

TECHNICAL DATA SHEET

PE44386

SSMA Female Connector Crimp/Solder Attachment For RG178, RG196

Configuration

ConnectorSSMA FemaleConnector SpecificationMIL-C-39012Connector Interface TypeRG178,RG196Cable Attachment Method (Shield/Contact)Crimp/SolderBody StyleStraight

Electrical Specifications

Impedance, Ohms 50

Mechanical Specifications

Temperature

Operating Range, deg C -65 to +165

Size

 Length, in [mm]
 0.8 [20.32]

 Width/Dia., in [mm]
 0.25 [6.35]

 Weight, lbs [g]
 0.006 [2.72]

Connector

Type SSMA Female
Contact Material and Plating Gold
Contact Plating Specification MIL-G-45204
Body Material and Plating Brass, Nickel
Dielectric Type Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

SSMA Female Connector Crimp/Solder Attachment For RG178, RG196 from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SSMA Female Connector Crimp/Solder Attachment For RG178, RG196 PE44386

URL: http://www.pasternack.com/ssma-female-standard-rg178-rg196-connector-pe44386-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

PE44386 CAD DrawingSSMA Female Connector Crimp/Solder Attachment For RG178, RG196

