



2.92mm Male Connector Solder Attachment for PECX001, PECX002, Low Loss 047 Semi-Rigid

RF Connectors Technical Data Sheet

PE45483

Configuration

- 2.92mm Male Connector
- 50 Ohms
- Straight Body Geometry
- Connector Interface Types: PECX001, PECX002

Features

- Max. Operating Frequency 45 GHz
- Excellent VSWR of 1.14:1
- Gold Plated Beryllium Copper Contact
- Contact plating according to ASTM-B488

Applications

- General Purpose Test
- Custom Cable Assemblies

Description

Pasternack's PE45483 2.92mm male connector with solder attachment for PECX001 and PECX002 is part of our full line of RF components available for same-day shipping. Our 2.92mm male connector operates up to a maximum frequency of 45 GHz and offers excellent VSWR of 1.14:1.

Our 2.92mm male connector PE45483 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		45	GHz
VSWR			1.14:1	
Dielectric Withstanding Voltage (AC)			500	Vrms
High Potential Voltage			325	Vrms
Corona Discharge			125	Vrms
Insulation Resistance	5,000			MOhms
RF Leakage	-90			dB

Performance by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	DC to 18	18 to 26.5	26.5 to 45			GHz
VSWR, Max	1.1:1	1.12:1	1.14:1			

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.92mm Male Connector Solder Attachment for PECX001, PECX002, Low Loss 047 Semi-Rigid PE45483](#)



2.92mm Male Connector Solder Attachment for PECX001, PECX002, Low Loss 047 Semi-Rigid

RF Connectors Technical Data Sheet

PE45483

Electrical Specification Notes:
Insertion Loss = $0.04 \times \sqrt{\text{Fghz}}$ dB

Mechanical Specifications

Size

Length 0.54 in [13.72 mm]
Width/Dia. 0.35 in [8.89 mm]

Mating Cycles 500 Cycles
Mating Torque 8 to 10 in-lbs [0.90 to 1.13 Nm]

Material Specifications

Description	Material	Plating
Contact	Beryllium Copper	Gold ASTM-B488
Insulation	PTFE	
Body	Beryllium Copper	Gold ASTM-B488
Coupling Nut	Steel	
Gasket	Silicone Rubber	

Environmental Specifications

Temperature

Operating Range -65 to +165 deg C
Shock MIL-STD-202, Method 213, Condition I
Vibration MIL-STD-202, Method 204, Condition D
Thermal Shock MIL-STD-202, Method 107, Condition B

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.92mm Male Connector Solder Attachment for PECX001, PECX002, Low Loss 047 Semi-Rigid PE45483](#)




2.92mm Male Connector Solder Attachment for PECX001, PECX002, Low Loss 047 Semi-Rigid

RF Connectors Technical Data Sheet

PE45483

Assembly Instruction




STEP 1:

- PRE-TIN CABLE OUTER JACKET OVER APPROX. LENGTH SHOWN.
- TRIM CABLE TO EXPOSE CENTER CONDUCTOR AS SHOWN.
- POINT CENTER CONDUCTOR AS INDICATED.
- SLIDE DIELECTRIC STOP ONTO CENTER CONDUCTOR AGAINST OUTER JACKET.

STEP 2:

- INSERT CABLE INTO CONNECTOR UNTIL CENTER CONDUCTOR PLUGS IN AND CABLE SEATS IN CONNECTOR BORE.
- SOLDER CABLE JACKET TO BODY WHERE SHOWN APPLYING HEAT TO EXTENDED BODY TAIL.



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.92mm Male Connector Solder Attachment for PECX001, PECX002, Low Loss 047 Semi-Rigid PE45483](#)



2.92mm Male Connector Solder Attachment for PECX001, PECX002, Low Loss 047 Semi-Rigid

RF Connectors Technical Data Sheet

PE45483

2.92mm Male Connector Solder Attachment for PECX001, PECX002, Low Loss 047 Semi-Rigid from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [2.92mm Male Connector Solder Attachment for PECX001, PECX002, Low Loss 047 Semi-Rigid PE45483](https://www.pasternack.com/2.92mm-male-pecx001-pecx002-connector-pe45483-p.aspx)

URL: <https://www.pasternack.com/2.92mm-male-pecx001-pecx002-connector-pe45483-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

PE45483 CAD Drawing

2.92mm Male Connector Solder Attachment for PECX001,
PECX002, Low Loss 047 Semi-Rigid



STANDARD TOLERANCES	
.X	±0.2
.XX	±0.01
.XXX	±0.005

*STANDARD TOLERANCES APPLY ONLY TO DIMENSIONS IN INCHES

NOTES: DISTANCE FROM END OF CABLE CENTER COND. TO REF. PL. IS .290

NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].



Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | Fax: (949) 261-7451
Website: www.pasternack.com | E-Mail: sales@pasternack.com

DWG TITLE
PE45483

CAGE CODE 53919

CAD FILE 07/27/18

SCALE N/A

SIZE A

CN2379