



# N Female Connector Clamp/Solder Attachment for RG14, RG217

## RF Connectors Technical Data Sheet

PE4645

# Configuration

- N Female Connector
- MIL-STD-348
- 50 Ohms

- Straight Body Geometry
- RG14, RG217 Interface Type
- Clamp/Solder Attachment

### **Features**

Silver Plated Contact

Contact plating according to QQ-S-365

# **Applications**

• General Purpose Test

Custom Cable Assemblies

### Description

Pasternack's PE4645 type N female connector with clamp/solder attachment for RG14 and RG217 is part of our full line of RF components available for same-day shipping.

Our type N female connector PE4645 datasheet specifications and drawing with dimensions are shown below in this PDF. Pasternack's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Pasternack has the right connector for the job. Pasternack can also expertly build your custom cable assemblies for you and ship same-day.

### **Mechanical Specifications**

Size

 Length
 1.78 in [45.21 mm]

 Width/Dia.
 0.875 in [22.23 mm]

 Weight
 0.151 lbs [68.49 g]

### **Material Specifications**

Description		Material	Plating
Contact			Silver QQ-S-365
Insulation		PTFE	
Body		Brass	Nickel QQ-N-290

### **Environmental Specifications**

**Temperature** 

Operating Range -65 to +165 deg C

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Female Connector Clamp/Solder Attachment for RG14, RG217 PE4645

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

Sales@Pasternack.com • Techsupport@Pasternack.com





# N Female Connector Clamp/Solder Attachment for RG14, RG217

# RF Connectors Technical Data Sheet

PE4645

Compliance Certifications (see product page for current document)

### **Plotted and Other Data**

Notes:

N Female Connector Clamp/Solder Attachment for RG14, RG217 from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Female Connector Clamp/Solder Attachment for RG14, RG217 PE4645


URL: https://www.pasternack.com/n-female-standard-rg14-rg217-connector-pe4645-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.


Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451

# ASSEMBLY PROCEDURES

(3) SLIDE BRAID CLAMP(3) OVER BRAID & SEAT SLIDE CLAMP NUT (1) & GASKET (2) OVER CABLE. STRIP CABLE AS SHOWN. DO NOT NICK BRAID WHILE CUTTING JACKET. TAPER END OF BRAID TO PERMIT ASSEMBLY OF BRAID CLAMP AGAINST CABLE.



OVER HEAT DIELECTRIC. INSERT CABLE ASSEMBLY INTO BODY & TIGHTEN. BRAID OVER CLAMP NUT (3). TRIM BRAID DIMENSION SHOWN. DO NOT NICK CENTER CONDUCTOR. SOLDER CONTACT TO CENTER CONDUCTOR. REMOVE EXCESS SOLDER. DO NOT TO SHOULDER. CUT DIELECTRIC TO FORM BACK





DWG TITLE

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES (mm).
4. FITS MIL-C-17 AND EQUIVALENT CABLES.

XXX

SIZE

SCALE N/A

042309

CAD FILE

53919

FSCM NO.

Pasternack Enterprises, Inc. P.O. Box 16759 | Irvine | CA | 92623

Website: www.pasternack.com | E-Mail: sales@pasternack.com Phone: (949) 261-1920 | Fax: (949) 261-7451

ä