



50 Ohm 10 Watts Aluminum Heatsink BNC Female RF Load Up To 4 GHz

TECHNICAL DATA SHEET

PE6101

Configuration	
Connector	BNC Female
Connector Specification	MIL-STD-348
Heat Sink	Aluminum Heatsink, Black Anodized
Electrical Specifications	
Frequency Range, GHz	DC to 4
Impedance, Ohms	50
Maximum VSWR	1.25:1
Maximum Input Power, Watts	10
Peak Power, Watts	500
Mechanical Specifications	
Temperature	
Operating Range, deg C	-65 to +125
Size	
Length, in [mm]	1.73 [43.94]
Width/Dia., in [mm]	1 [25.4]
Connector	
Туре	BNC Female
Body Material and Plating	Brass, Nickel
Compliance Certifications (visit www.Pasternac	k.com for current document)
RoHS Compliant	Yes
Plotted and Other Data	
Notes:	Values at 25 °C, sea level
	e RF Load Up To 4 GHz from Pasternack Enterprises has same day RF, microwave and fiber optic products maintain a 99% availability and
	ARCH" on website) to obtain additional part information including price, um Heatsink BNC Female RF Load Up To 4 GHz PE6101
URL: http://www.pasternack.com/bnc-female-high-pc	ower-termination-pe6101-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com

PE6101 CAD Drawing 50 Ohm 10 Watts Aluminum Heatsink BNC Female RF Load Up To 4 GHz

