



# Medium Power 50 Watts RF Load Up To 18 GHz With N Female Input Square Body Black Anodized Aluminum Heatsink

### **TECHNICAL DATA SHEET**

**PE6214** 

#### Configuration

Connector N Female
Connector Specification MIL-STD-348

Heat Sink Black Anodized Aluminum Heatsink

Connection Method Standard Body Style Straight

#### **Electrical Specifications**

Frequency Range, GHz
Impedance, Ohms
50
Maximum VSWR
1.6:1
Maximum Input Power, Watts
50
Peak Power, Watts
500

#### Frequency 1

Frequency, GHz DC to 6 VSWR 1.3:1

#### Frequency 2

Frequency, GHz 6 to 12.4 VSWR 1.45:1

#### Frequency 3

Frequency, GHz 12.4 to 18 VSWR 1.6:1

#### **Mechanical Specifications**

#### Temperature

Operating Range, deg C -65 to +125
Color Black

#### Connector

Type N Female

Inner Conductor Material and Plating

Outer Conductor Material and Plating

Body Material and Plating

Beryllium Copper, Gold

Passivated Stainless Steel

Passivated Stainless Steel

Dielectric Type PTFE

#### Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Medium Power 50 Watts RF Load Up To 18 GHz With N Female Input Square Body Black Anodized Aluminum Heatsink PE6214

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com





# Medium Power 50 Watts RF Load Up To 18 GHz With N Female Input Square Body Black Anodized Aluminum Heatsink

### **TECHNICAL DATA SHEET**

**PE6214** 

#### **Plotted and Other Data**

Notes:

Values at 25 °C, sea level

Medium Power 50 Watts RF Load Up To 18 GHz With N Female Input Square Body Black Anodized Aluminum Heatsink from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Medium Power 50 Watts RF Load Up To 18 GHz With N Female Input Square Body Black Anodized Aluminum Heatsink PE6214

URL: http://www.pasternack.com/50-watts-n-female-rf-load-up-to-18-ghz-pe6214-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com

## PE6214 CAD Drawing

Medium Power 50 Watts RF Load Up To 18 GHz With N Female Input Square Body Black Anodized Aluminum Heatsink

