



5 Watt RF Load Up to 12.4 GHz With N Female Input Aluminum Body

RF Terminations Technical Data Sheet

PE6TR1133

Features

- DC to 12.4GHz Frequency Range
- 50 Ohm Impedance
- N Female Coaxial Interface
- Max VSWR 1.25:1
- Max Power 5 Watts (CW)

Applications

- WIFI 6E
- 5G Cellular Bands
- SatCom
- Radar Systems
- Test and Measurement
- Commercial and Military
- Communication

Description

Pasternack's PE6TR1133 is an RF termination (also called RF load or dummy load) that operates from DC to 12.4 GHz and handles up to 5 Watt (CW). Our N termination / load has a female gender. PE6TR1133 N load termination offers 1.25:1 max VSWR.

RF load / terminations are indispensable components in many RF, microwave and millimeter wave systems where signal reflection from unused ports can potentially damage the device or reduce the signal integrity. By using a terminator on an unused port with a matched load (dummy load), the incident energy will be absorbed with minimal reflection. These termination components are commonly used to terminate devices such as couplers, circulators, and switches. They are also widely used in measurement systems to ensure accurate results. Pasternack offers a huge selection of RF, microwave and millimeter wave terminations up to 65 GHz with excellent performance over the entire operating range and power handling capabilities up to 800 Watt (CW).

Electrical Specifications

| Description | Minimum | Typical | Maximum | Units |
|---|---------|---------|---------|--------|
| Frequency Range | DC | | 12.4 | GHz |
| Impedance | | 50 | | Ohms |
| VSWR | | | 1.25:1 | |
| Input Power (CW) Derated linearly to 0.5W at 125°C | | | 5 | Watts |
| Input Power (Peak) 5 μ s pulse, 0.25% Duty Cycle | | | 1 | kWatts |

Mechanical Specifications

| | |
|-------------|--------------------|
| Size | |
| Length | 2.05 in [52.07 mm] |
| Width | 0.71 in [18.03 mm] |
| Height | 0.71 in [18.03 mm] |
| Weight | 0.17 lbs [77.11 g] |

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [5 Watt RF Load \(Termination\) Up to 12.4 GHz With N Female Input Aluminum Body PE6TR1133](#)



5 Watt RF Load Up to 12.4 GHz With N Female Input Aluminum Body

RF Terminations Technical Data Sheet

PE6TR1133

Configuration

Connector

N Female

Termination Design

RF Load

Material Specifications

| Description | Material | Plating |
|---------------------|------------------|---------|
| Connector 1 Contact | Beryllium Copper | Gold |
| Body | Aluminum | |
| Housing | Aluminum | |

Environmental Specifications

Temperature

Operating Range

-55 to +85 deg C

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

5 Watt RF Load Up to 12.4 GHz With N Female Input Aluminum Body from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [5 Watt RF Load \(Termination\) Up to 12.4 GHz With N Female Input Aluminum Body PE6TR1133](#)

URL: <https://www.pasternack.com/5-watts-n-female-rf-load-12.4-ghz-pe6tr1133-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.


PE6TR1133 CAD Drawing

5 Watt RF Load Up to 12.4 GHz With N Female Input Aluminum Body

F E D C B A

F E D C B A

| REVISION | | | |
|----------|------|-----------------|-------------|
| ZONE | REV. | DESCRIPTION | DATE |
| | A | INITIAL RELEASE | 01/30/2023 |
| | | CHANGED BY | APPROVED BY |
| | | DMAY | SPONG |



| | |
|--|---------------------|
| UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS | |
| X = ±.2 [5] | FRACTIONS ± 1/32 |
| .XX = ±.02 [.5] | ANGLES ± 1° |
| .XXX = ±.005 [.13] | |
| CABLE LENGTH TOLERANCES: | |
| >12 [305] = +1 [25] / -0 | |
| >12 [305] ≤ 60 [1524] = +2 [51] / -0 | |
| >60 [1524] ≤ 120 [3048] = +4 [102] / -0 | |
| >120 [3048] ≤ 300 [7620] = +6 [152] / -0 | |
| >300 [7620] = +5% / -0 | |
| ALL DIMENSIONS ARE FOR REFERENCE ONLY AND SUBJECT TO CHANGE WITHOUT NOTICE | |



an INFINITI® brand

Website: www.Pasternack.com

Phone: 1.866.727.8376 | 1.949.261.1920

| | |
|---|--------|
| INTERPRET ALL DIMENSIONS AND TOLERANCES PER ASME Y14.5 | |
| SCALE | NONE |
| SHEET | 1 OF 1 |

| | | | |
|---|-----------|----------|-----------|
| DESCRIPTION N FEMALE TERMINATION, ALUMINUM BODY RATED TO 5 WATTS UP TO 12.4 GHz | | | |
| SIZE | CAGE CODE | DRAWN BY | ITEM NO. |
| A | 53919 | DMAY | PE6TR1133 |
| | | | REV |
| | | | A |

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF INFINITE ELECTRONICS, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF INFINITE ELECTRONICS, INC. IS PROHIBITED. THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.