

# Product data sheet

## Characteristics

# 9001SK43J32LGG

## selector switch Ø 30 - 3 positions - maintained - LED



### Main

|                           |                     |
|---------------------------|---------------------|
| Range of Product          | Harmony 9001SK      |
| Product or Component Type | Selector switch     |
| Device short name         | 9001SK              |
| Type of operator          | maintained          |
| Operator profile          | Green standard knob |

### Complementary

|                               |                            |
|-------------------------------|----------------------------|
| Bezel material                | Plastic                    |
| Mounting diamete              | 1.2 in (30 mm)             |
| Net Weight                    | 0.540 lb(US) (0.245 kg)    |
| Shape of signaling unit head  | Round                      |
| Operator position information | 3 positions                |
| Contacts type and composition | Without contact block      |
| Mechanical durability         | 500000 cycles              |
| Light block supply            | Direct                     |
| Light source                  | LED                        |
| Bulb base                     | BA 9s                      |
| Light block colour            | Green                      |
| Signalling type               | LED                        |
| [Us] rated supply voltage     | 12...14 V AC/DC 50...60 Hz |
| Device presentation           | Basic element              |
| Compatibility code            | 9001SK                     |

### Environment

|                                       |  |
|---------------------------------------|--|
| Protective treatment                  | TC   |
| Ambient Air Temperature for Storage   | -40...158 °F (-40...70 °C)   |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C)   |
| Electrical shock protection class     | Class II IEC 61140   |
| IP degree of protection               | IP66 IEC 60529   |
| NEMA degree of protection             | NEMA 1<br>NEMA 12<br>NEMA 13<br>NEMA 2<br>NEMA 3<br>NEMA 3R<br>NEMA 4<br>NEMA 6                                |
| Standards                             | UL 508<br>CSA C22.2 No 14<br>JIS C 4520<br>EN/IEC 60947-1<br>EN/IEC 60947-5-4<br>EN/IEC 60947-5-1<br>JIS C 852 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                        |                               |
|------------------------|-------------------------------|
| Product Certifications | UL 508[RETURN]NEMA            |
| Vibration resistance   | 7 gn 2...500 Hz)IEC 60068-2-6 |
| Shock resistance       | 50 gn IEC 60068-2-27          |

### Ordering and shipping details

|                   |              |
|-------------------|--------------|
| Category          | US10CS121433 |
| Discount Schedule | 0CS1         |
| GTIN              | 785901581734 |
| Returnability     | No           |
| Country of origin | MX           |

### Packing Units

|                              |                    |
|------------------------------|--------------------|
| Unit Type of Package 1       | PCE                |
| Number of Units in Package 1 | 1                  |
| Package 1 Height             | 3.63 in (9.208 cm) |
| Package 1 Width              | 1.81 in (4.604 cm) |
| Package 1 Length             | 2.13 in (5.398 cm) |
| Package 1 Weight             | 8.6 oz (245 g)     |

### Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           |  <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a>  |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>  |
| RoHS exemption information |  Yes   |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | No need of specific recycling operations  |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|