SIEMENS

Data sheet US2:52BP3CZ



30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Illuminated Push-Pull Operator Full Voltage, 12V AC/DC Incandescent Lamp Less Mushroom Head Cap 3 Position Momentary UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

design of the product	Actuator round	
Enclosure		
number of command points	1	
delivery state as a kit	No	
Actuator		
product extension optional light source	Yes	
type of unlocking device	without	
number of switching positions	3	
Front ring		
product component front ring	Yes	
design of the front ring	standard	
material of the front ring	metal	
color of the front ring	black	
Holder		
material of the holder	Metal	
Contact block/ lampholder		
socket design	BA 9s with lamp	
number of lampholders	1	
Display		
number of LED modules	0	
General technical data		
product component		
lamp transformer	No	
• light source	Yes	
degree of pollution	1	
type of voltage		
 of the operating voltage 	AC/DC	
of the input voltage	AC/DC	
surge voltage resistance rated value	4 kV	
protection class IP	IP66	
of the terminal		
	IP20	
operating voltage		
• at AC at 60 Hz rated value	12 13 V	
at AC at 60 Hz rated valueat DC rated value		
at AC at 60 Hz rated value at DC rated value Supply voltage	12 13 V 12 13 V	
at AC at 60 Hz rated valueat DC rated value	12 13 V	
at AC at 60 Hz rated value at DC rated value Supply voltage	12 13 V 12 13 V	
at AC at 60 Hz rated value at DC rated value Supply voltage type of voltage of the supply voltage of the light source supply voltage of the light source at AC at 60 Hz rated value •	12 13 V 12 13 V	
at AC at 60 Hz rated value at DC rated value Supply voltage type of voltage of the supply voltage of the light source supply voltage of the light source at AC at 60 Hz rated value	12 13 V 12 13 V AC/DC	

Connections/ Terminals	
type of electrical connection	screw terminal
of modules and accessories	Screw-type terminal
tightening torque of the screws in the bracket maximum	20 N·m
tightening torque [lbf·in] with screw-type terminals	8 8 lbf·in
Lamp	
type of light source	filament lamp
color of the light source	clear
Electrical Safety	
touch protection against electrical shock	finger-safe
Ambient conditions	
ambient temperature	
 during operation 	-35 +70 °C
during storage	-40 +85 °C
Installation/ mounting/ dimensions	
shape of the installation opening	round
Further information	

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52BP3CZ

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52BP3CZ

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/US2:52BP3CZ

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52BP3CZ&lang=en

last modified:	4/8/2024
iast mounieu.	4/8/2024 C