SIEMENS

Data sheet

US2:52PP2BS

	30mm Command/52, Chrome Finish Heavy Duty,Watertight/Oiltight Complete Metal Unit Illuminated Push-Pull Operator Full Voltage, 6V AC/DC Incandescent Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Plastic, Green 2 Position Maintained, Pull-to-Release UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards
design of the product	Actuator round
Enclosure	
number of command points	1
delivery state as a kit	No
Actuator	
product extension optional light source	Yes
material of the actuating element	plastic
type of unlocking device	pull-to-unlatch mechanism
number of switching positions	2
Front ring	
product component front ring	Yes
design of the front ring	standard
material of the front ring	metal
color of the front ring	chrome
Holder	
material of the holder	Metal
Contact block/ lampholder	Weta
	PA 0a with Jamp
socket design	BA 9s with lamp
number of lampholders	1
Display	<u>^</u>
number of LED modules	0
General technical data	
product component	
lamp transformer	No
light source	Yes
degree of pollution	1
type of voltage	
 of the operating voltage 	AC/DC
 of the input voltage 	AC/DC
surge voltage resistance rated value	4 kV
protection class IP	IP66
of the terminal	IP20
operating voltage	
 at AC at 60 Hz rated value 	6 8 V
 at DC rated value 	6 8 V
Supply voltage	
type of voltage of the supply voltage of the light source	AC/DC
supply voltage of the light source at AC at 60 Hz rated value	
•	8 6 V
supply voltage of the light source at DC rated value	
•	8 6 V
Connections/ Terminals	
type of electrical connection	screw terminal
 of modules and accessories 	Screw-type terminal
tightening torque of the screws in the bracket maximum	20 N·m
tightening torque [lbf-in] with screw-type terminals	8 8 lbf·in
Lamp	
type of light source	filament lamp
-JE- of light course	in a non- tomp

color of the light source	clear
Electrical Safety	
touch protection against electrical shock	finger-safe
Ambient conditions	
ambient temperature	
 during operation 	-35 +70 °C
 during storage 	-40 +85 °C
Installation/ mounting/ dimensions	
shape of the installation opening	round
Further information	
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/10981387 Information- and Downloadcenter (Catalogs, Brochures,) https://www.siemens.com/ic10 Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?/ Cax online generator http://support.automation.siemens.com/WW/CAXorder/default. Service&Support (Manuals, Certificates, Characteristics, F https://support.industry.siemens.com/cs/ww/en/ps/US2:52PP2f Image database (product images, 2D dimension drawings,) mlfb=US2:52PP2BS aspx?lang=en&mlfb=US2:52PP2BS AQs,) BS
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52PP2BS⟨=en	

last modified:

4/8/2024 🖸