



Selector switch, metal, NEMA 4X Spring return from right Short lever, C Cam 3 position Operator only white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)

|                                           |                             |
|-------------------------------------------|-----------------------------|
| design of the product                     | Actuator round              |
| <b>Enclosure</b>                          |                             |
| number of command points                  | 1                           |
| delivery state as a kit                   | No                          |
| <b>Actuator</b>                           |                             |
| design of the actuating element           | selector switch             |
| material of the actuating element         | plastic                     |
| type of unlocking device                  | rotate-to-unlatch mechanism |
| number of switching positions             | 3                           |
| <b>Front ring</b>                         |                             |
| product component front ring              | Yes                         |
| design of the front ring                  | standard                    |
| material of the front ring                | metal                       |
| color of the front ring                   | black                       |
| <b>Holder</b>                             |                             |
| material of the holder                    | Metal                       |
| <b>General technical data</b>             |                             |
| product component                         |                             |
| • light source                            | No                          |
| degree of pollution                       | 1                           |
| protection class IP                       | IP66                        |
| operating frequency maximum               | 600 1/h                     |
| <b>Ambient conditions</b>                 |                             |
| ambient temperature                       |                             |
| • during operation                        | -35 ... +70 °C              |
| • during storage                          | -40 ... +85 °C              |
| <b>Installation/ mounting/ dimensions</b> |                             |
| shape of the installation opening         | round                       |
| <b>Further information</b>                |                             |

### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SX2CCB>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SX2CCB>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SX2CCB>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=US2:52SX2CCB&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SX2CCB&lang=en)

