## **SIEMENS**

## **Data sheet**



Selector switch, illuminable, 22 mm, round, plastic with metal front ring, green, selector switch, short, 3 switch positions I-O<II, left latching, right momentary contact type, actuating angle 2x45°, 10:30h/12h/13:30h, with laser labeling, upper case and lower case, always upper case at the beginning of the word

product brand name	SIRIUS ACT	
product designation	Selector switches	
design of the product	Actuating/signaling element	
product type designation	3SU1	
product line	Plastic with metal front ring, matt, 22 mm	
Enclosure		
number of command points	1	
Actuator		
design of the actuating element	Selector, short	
principle of operation of the actuating element	latching/momentary contact, $2x45^{\circ}$ (10:30 h/12 h/13:30 h), return from right, left latching	
product extension optional		
• light source	Yes	
contact module	Yes	
color of the actuating element	green	
material of the actuating element	plastic	
shape of the actuating element	Handle	
outer diameter of the actuating element	32.3 mm	
marking of the actuating element	Customized labeling, text in lower case / capital letters, all words start with capital letters	
number of switching positions	3	
actuating angle		
• clockwise	45°	
anticlockwise	45°	
Front ring		
product component front ring	Yes	
design of the front ring	standard	
material of the front ring	Metal, matt	
color of the front ring	sand gray	
General technical data		
protection class IP	IP66, IP67, IP69(IP69K)	
degree of protection NEMA rating	1, 2, 3, 3R, 4, 4X, 12, 13	
shock resistance		
<ul> <li>according to IEC 60068-2-27</li> </ul>	sinusoidal half-wave 15g / 11 ms	
<ul> <li>for railway applications according to EN 61373</li> </ul>	Category 1, Class B	
vibration resistance		
<ul><li>according to IEC 60068-2-6</li></ul>	10 500 Hz: 5g	
<ul> <li>for railway applications according to EN 61373</li> </ul>	Category 1, Class B	
operating frequency maximum	1 800 1/h	
mechanical service life (operating cycles) typical	1 000 000	
reference code according to IEC 81346-2	S	

	10/04/0044	
Substance Prohibitance (Date)	10/01/2014	
Safety related data		
B10 value with high demand rate according to SN 31920	300 000	
proportion of dangerous failures		
<ul> <li>with low demand rate according to SN 31920</li> </ul>	20 %	
with high demand rate according to SN 31920	20 %	
failure rate [FIT] with low demand rate according to SN 31920	100 FIT	
Ambient conditions		
ambient temperature		
<ul> <li>during operation</li> </ul>	-25 +70 °C	
during storage	-40 +80 °C	
environmental category during operation according to IEC 60721	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%)	
Installation/ mounting/ dimensions		
height	32.3 mm	
width	32.3 mm	
shape of the installation opening	round	
mounting diameter	22.3 mm	
positive tolerance of installation diameter	0.4 mm	
mounting height	28.8 mm	
installation width	32.3 mm	
installation depth	25.4 mm	
Certificates/ approvals		
Further information		

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1032-2BN40-0AA0-Z Y15

Cax online generator

 $\underline{\text{http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en\&mlfb=3SU1032-2BN40-0AA0-Z\ Y15}$ 

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1032-2BN40-0AA0-Z Y15

 $Image\ database\ (product\ images,\ 2D\ dimension\ drawings,\ 3D\ models,\ device\ circuit\ diagrams,\ EPLAN\ macros,\ ...)$ 

http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SU1032-2BN40-0AA0-Z Y15&lang=en

last modified:	1/26/2022 🗗
----------------	-------------