SIEMENS

Data sheet



RONIS key-operated switch, 22 mm, round, metal, shiny, special lock, with 2 keys, 3 switch positions I-O-II, latching, actuating angle $2x45^{\circ}$, 10:30h/12h/13:30h, key removal O, possible special locks: SB31, 421, 455

product brand name dosign of the product dosign of the product product type designation product type designation product time product time Actuating/signaling element product time Actuation Actuati		
design of the product product type designation product line Metal, shiny, 22 mm Actuator principle of operation of the actuating element product extension optional light source color • of the actuating element material of the actuating element sliver material of the actuating element shape of the actuating element shape of the actuating element shape of the actuating element couter diameter of the actuating element shape of the actuating element shape of the actuating element couter diameter of the actuating element shape of the actuating element couter diameter couter d	product brand name	SIRIUS ACT
product type designation product line Metal, shiny, 22 mm Actuator principle of operation of the actuating element product extension optional light source of the actuating element material of the actuating element silver material of the actuating element shape of the actuating element wetal shape of the actuating element shape of the actuating element wetal shape of the actuating element wetal shape of the actuating element yetal shape of the actuating element wetal shape of the actuating element yetal yetal shape of the actuating element yetal yet	product designation	Key-operated switches
product line Actuator principle of operation of the actuating element product extension optional light source of the actuating element material of the actuating element shape of the actuating element shape of the actuating element shape of the actuating element waterial of the actuating element shape of the a	design of the product	Actuating/signaling element
Actuator principle of operation of the actuating element product extension optional light source No color • of the actuating element sliver material of the actuating element metal shape of the actuating element (Key) outer diameter of the actuating element (Sey) outer diameter of the actuating el	product type designation	3SU1
principle of operation of the actuating element product extension optional light source of the actuating element of the actuating element sliver material of the actuating element shape of the actuating element shape of the actuating element shape of the actuating element couter diameter of the actuating element number of switching positions 3 switch position for key distraction o actuating angle olockwise solickwise solickwise solickwise solick make RONIS Front ring product component front ring design of the front ring material of the front ring sliver General technical data protection class IP of the terminal degree of protection NEMA rating shock resistance according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms substance Prohibitance (Date) Ambient conditions ambient temperature olduring operation v25 *70 °C latching apperation	product line	Metal, shiny, 22 mm
product extension optional light source color of the actuating element material of the actuating element shape of the actuating element shape of the actuating element well shape of the actuating element shape of the actuating element outer diameter of the actuating element number of switching positions 3 switch position for key distraction octuating angle octockwise actuating angle octockwise actuating angle octockwise shape octockwise octockwise octockwise octockwise octockwise octockwise octockwise octor of the front ring well design of the front ring slandard material of the front ring well design of the front ring octor of the front ring octor of the front ring octor of the front ring of the terminal degree of protection NEMA rating of the terminal degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13 shock resistance • according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms vibration resistance • according to IEC 60068-2-6 operating frequency maximum nechanical service life (operating cycles) typical reference code according to IEC 81346-2 S Substance Prohibitance (Date) • during operation - 25 +70 °C	Actuator	
color • of the actuating element metal shape of the actuating element Key outer diameter of the actuating element 29,5 mm number of switching positions 3 switch position for key distraction O actuating angle • clockwise 45° lock make RONIS Front ring product component front ring Yes design of the front ring Standard material of the front ring Metal, high gloss color of the front ring IP20 General technical data protection class IP IP20 degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13 shock resistance • according to IEC 60068-2-6 10 500 Hz: 5g operating frequency maximum 1 800 000 substance Prohibitance (Date) Ambient conditions ambient temperature • during operation -25 +70 °C	principle of operation of the actuating element	latching, 2x45° (10:30 h/12 h/13:30 h)
• of the actuating element metal shape of the actuating element Key outer clameter of the actuating element 29.5 mm number of switching positions 3 switch position for key distraction O actuating angle • clockwise 45° • anticlockwise 45° lock make RONIS Front ring product component front ring Standard material of the front ring Silver General technical data protection class IP • of the terminal IP20 degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13 shock resistance • according to IEC 60068-2-6 operating frequency maximum 1800 1/h mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) - ambient temperature • during operation - 25 +70 °C	product extension optional light source	No
material of the actuating element Key outer diameter of the actuating element 29.5 mm number of switching positions 3 switch position for key distraction O actuating angle • clockwise 45° • anticlockwise 45° lock make RONIS Front ring product component front ring Standard material of the front ring Metal, high gloss color of the front ring Silver General technical data protection class IP • of the terminal IP20 degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13 shock resistance • according to IEC 60068-2-6 10 500 Hz: 5g coperating frequency maximum 1800 1/h mechanical service life (operating cycles) typical 300 000 reference code according to IEC 81346-2 S Substance Portoiltons ambient temperature • during operation • 25 +70 °C	color	
shape of the actuating element outer diameter of the actuating element number of switching positions switch position for key distraction octuating angle clockwise clockwise define enticlockwise front ring product component front ring design of the front ring material of the front ring sliver General technical data protection class IP of the terminal degree of protection NEMA rating shock resistance eacording to IEC 60068-2-6 operating frequency maximum nechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Put in the prost temporature oduring operation Rey eduring operation Rey 29.5 mm 29.5 mm	of the actuating element	silver
outer diameter of the actuating element number of switching positions switch position for key distraction octuating angle clockwise clockwise clockwise design of the front ring material of the front ring material of the front ring silver General technical data protection class IP of the terminal degree of protection NEMA rating shock resistance according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) ambient temperature during operation 29.5 mm 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	material of the actuating element	metal
number of switching positions switch position for key distraction otuating angle e clockwise e anticlockwise front ring product component front ring design of the front ring material of the front ring silver General technical data protection class IP e of the terminal degree of protection NEMA rating shock resistance e according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms vibration resistance e according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibilance (Date) Ambient conditions ambient temperature e during operation	shape of the actuating element	Key
switch position for key distraction actuating angle • clockwise • anticlockwise • anticlockwise • anticlockwise • anticlockwise Iok make RONIS Front ring product component front ring design of the front ring material of the front ring material of the front ring color of the front ring general technical data protection class IP • of the terminal degree of protection NEMA rating shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature • during operation	outer diameter of the actuating element	29.5 mm
actuating angle • clockwise • anticlockwise • anticlockwise Iok make RONIS Front ring product component front ring design of the front ring material of the front ring General technical data protection class IP • of the terminal degree of protection NEMA rating shock resistance • according to IEC 60068-2-27 vibration resistance • according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient temperature • during operation -25 +70 °C	number of switching positions	3
o clockwise o anticlockwise o anticlockwise lock make RONIS Front ring product component front ring design of the front ring material of the front ring material of the front ring silver General technical data protection class IP of the terminal of the terminal lep20 degree of protection NEMA rating shock resistance o according to IEC 60068-2-27 vibration resistance o according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature o during operation -25 +70 °C	switch position for key distraction	0
lock make RONIS Front ring product component front ring Yes design of the front ring Standard material of the front ring Metal, high gloss color of the front ring silver General technical data protection class IP of the terminal IP20 degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13 shock resistance • according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms vibration resistance • according to IEC 60068-2-6 10 500 Hz: 5g operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 S Substance Prohibitance (Date) 10/01/2014 Ambient conditions ambient temperature • during operation - 25 +70 °C	actuating angle	
lock make RONIS Front ring product component front ring Yes design of the front ring Standard material of the front ring Metal, high gloss color of the front ring silver General technical data protection class IP IP66, IP67, IP69(IP69K) • of the terminal IP20 degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13 shock resistance • according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms vibration resistance • according to IEC 60068-2-6 10 500 Hz: 5g operating frequency maximum mechanical service life (operating cycles) typical 300 000 reference code according to IEC 81346-2 S Substance Prohibitance (Date) 10/01/2014 Ambient conditions ambient temperature • during operation -25 +70 °C	• clockwise	45°
product component front ring Yes design of the front ring Standard material of the front ring Metal, high gloss color of the front ring silver General technical data protection class IP IP66, IP67, IP69(IP69K) of the terminal IP20 degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13 shock resistance according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms vibration resistance according to IEC 60068-2-6 10 500 Hz: 5g operating frequency maximum 1 800 1/h mechanical service life (operating cycles) typical 300 000 reference code according to IEC 81346-2 S Substance Prohibitance (Date) 10/01/2014 Ambient conditions ambient temperature o during operation -25 +70 °C	anticlockwise	45°
product component front ring design of the front ring material of the front ring material of the front ring Metal, high gloss color of the front ring gliver General technical data protection class IP of the terminal lP20 degree of protection NEMA rating shock resistance according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms vibration resistance according to IEC 60068-2-6 operating frequency maximum nechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature o during operation Standard Metal, high gloss Standard Metal, high gloss IP66, IP67, IP69(IP69K) IP20 IP20 IP66, IP67, IP69(IP69K) IP20 IP30 IP40 I	lock make	RONIS
design of the front ring material of the front ring material of the front ring color of the front ring silver General technical data protection class IP of the terminal lP20 degree of protection NEMA rating shock resistance according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms vibration resistance according to IEC 60068-2-6 10 500 Hz: 5g operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature during operation Sinusoidal half-wave 15g / 11 ms 1 800 1/h 1 800 1/h 1 800 1/h 2 9 3 00 000 3 0000 3 0000 3 0000 3 0000 4 0000 5 0000 6 00000 6 00000000000000000	Front ring	
material of the front ring color of the front ring silver General technical data protection class IP of the terminal legan degree of protection NEMA rating shock resistance according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms vibration resistance according to IEC 60068-2-6 10 500 Hz: 5g operating frequency maximum 1 800 1/h mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature during operation Metal, high gloss silver Metal, high gloss silver Metal, high gloss silver IP66, IP67, IP69(IP69K) IP20 IP69, IP69(IP69K) IP20 IP60, IP67, IP69(IP69K) IP20 IP60, IP67, IP69(IP69K) IP60, IP67, IP69(IP69K) IP60,	product component front ring	Yes
color of the front ring General technical data protection class IP of the terminal lP20 degree of protection NEMA rating shock resistance according to IEC 60068-2-27 vibration resistance according to IEC 60068-2-6 operating frequency maximum mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature other terminal lP20 IP66, IP67, IP69(IP69K) IP68, IP68, IP68, IP69(IP69K) IP68,	design of the front ring	Standard
protection class IP of the terminal liP20 degree of protection NEMA rating shock resistance according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms vibration resistance according to IEC 60068-2-6 10 500 Hz: 5g operating frequency maximum 1 800 1/h mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature during operation IP66, IP67, IP69(IP69K) IP20 IP66, IP67, IP69(IP69K) IP20 IP66, IP67, IP69(IP69K) IP20 IP66, IP67, IP69(IP69K) IP60, IP60, IP60, IP60, IP69(IP69K) IP60,	material of the front ring	Metal, high gloss
protection class IP of the terminal IP20 degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13 shock resistance oaccording to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms vibration resistance oaccording to IEC 60068-2-6 10 500 Hz: 5g operating frequency maximum 1 800 1/h mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature oduring operation IP20 IP20 IP20 IP20 In Source IP69(IP69K) In Source IP69(IP69K) In IP20	color of the front ring	silver
● of the terminal degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13 shock resistance ● according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms vibration resistance ● according to IEC 60068-2-6 10 500 Hz: 5g operating frequency maximum 1 800 1/h mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature ● during operation I, 2, 3, 3R, 4, 4X, 12, 13 30, 000 10 500 Hz: 5g 10 50	General technical data	
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13 shock resistance • according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms vibration resistance • according to IEC 60068-2-6 10 500 Hz: 5g operating frequency maximum 1 800 1/h mechanical service life (operating cycles) typical 300 000 reference code according to IEC 81346-2 S Substance Prohibitance (Date) 10/01/2014 Ambient conditions ambient temperature • during operation -25 +70 °C	protection class IP	IP66, IP67, IP69(IP69K)
shock resistance • according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms vibration resistance • according to IEC 60068-2-6 10 500 Hz: 5g operating frequency maximum 1 800 1/h mechanical service life (operating cycles) typical 300 000 reference code according to IEC 81346-2 S Substance Prohibitance (Date) 10/01/2014 Ambient conditions ambient temperature • during operation -25 +70 °C	of the terminal	IP20
according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms vibration resistance according to IEC 60068-2-6 10 500 Hz: 5g operating frequency maximum 1 800 1/h mechanical service life (operating cycles) typical 300 000 reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature during operation -25 +70 °C	degree of protection NEMA rating	1, 2, 3, 3R, 4, 4X, 12, 13
vibration resistance • according to IEC 60068-2-6 operating frequency maximum 1 800 1/h mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature • during operation 10 500 Hz: 5g 300 000 700 000 800 000 10/01/2014 -25 +70 °C	shock resistance	
 according to IEC 60068-2-6 10 500 Hz: 5g operating frequency maximum 1 800 1/h mechanical service life (operating cycles) typical 300 000 reference code according to IEC 81346-2 S Substance Prohibitance (Date) 10/01/2014 Ambient conditions ambient temperature • during operation -25 +70 °C 	according to IEC 60068-2-27	sinusoidal half-wave 15g / 11 ms
operating frequency maximum 1 800 1/h mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) 10/01/2014 Ambient conditions ambient temperature • during operation 1 800 1/h 300 000 10/01/2014 -25 +70 °C	vibration resistance	
mechanical service life (operating cycles) typical reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature • during operation 300 000 S 10/01/2014 Arc. -25 +70 °C	according to IEC 60068-2-6	10 500 Hz: 5g
reference code according to IEC 81346-2 Substance Prohibitance (Date) Ambient conditions ambient temperature • during operation -25 +70 °C	operating frequency maximum	1 800 1/h
Substance Prohibitance (Date) Ambient conditions ambient temperature • during operation -25 +70 °C	mechanical service life (operating cycles) typical	300 000
Ambient conditions ambient temperature • during operation -25 +70 °C	reference code according to IEC 81346-2	S
ambient temperature ● during operation -25 +70 °C	Substance Prohibitance (Date)	10/01/2014
• during operation -25 +70 °C	Ambient conditions	
3.45.44	ambient temperature	
• during storage -40 +80 °C	 during operation 	-25 +70 °C
	during storage	-40 +80 °C

environmental category during operation according to IEC 60721	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%)
Installation/ mounting/ dimensions	
height	29.5 mm
width	29.5 mm
shape of the installation opening	round
mounting diameter	22.3 mm
positive tolerance of installation diameter	0.4 mm
mounting height	49.4 mm
installation width	29.5 mm
installation depth	25.4 mm
Certificates/ approvals	
Further information	

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1050-4BL01-0AA0-Z Y01

Cax online generator

 $\underline{\text{http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en\&mlfb=3SU1050-4BL01-0AA0-Z~Y01-0AA$

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1050-4BL01-0AA0-Z Y01

 $Image\ database\ (product\ images,\ 2D\ dimension\ drawings,\ 3D\ models,\ device\ circuit\ diagrams,\ EPLAN\ macros,\ ...)$

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1050-4BL01-0AA0-Z Y01&lang=en

last modified:	1/26/2022 🖸
last modified:	1/26/2022