## SIEMENS

## Data sheet

## 3SU1050-1BA10-0AA0-Z Y12



Mushroom pushbutton, 22 mm, round, metal, shiny, black, 40 mm, latching, pull-to-unlatch mechanism, with laser labeling, lower case

| product brand name                                 | SIRIUS ACT                                      |
|--|---|
| product designation                                | Mushroom pushbuttons                            |
| design of the product                              | Actuating/signaling element                     |
| product type designation                           | 3SU1  |
| product line                                       | Metal, shiny, 22 mm                             |
| Enclosure  |   |
| number of command points                           | 1   |
| Actuator   |   |
| principle of operation of the actuating element    | latching  |
| product extension optional light source            | No  |
| color of the actuating element                     | black   |
| material of the actuating element                  | plastic   |
| shape of the actuating element                     | round   |
| outer diameter of the actuating element            | 40 mm   |
| marking of the actuating element                   | Customized labeling, text in lower case letters |
| type of unlocking device                           | pull-to-unlatch mechanism                       |
| number of switching positions                      | 2   |
| Front ring   |   |
| product component front ring                       | Yes   |
| design of the front ring                           | Standard  |
| material of the front ring                         | Metal, high gloss                               |
| color of the front ring                            | silver  |
| General technical data                             |   |
| product function                                   |   |
| <ul> <li>EMERGENCY OFF function</li> </ul>         | No  |
| EMERGENCY STOP function                            | No  |
| protection class IP                                | IP66, IP67, IP69(IP69K)                         |
| degree of protection NEMA rating                   | 1, 2, 3, 3R, 4, 4X, 12, 13                      |
| shock resistance                                   |   |
| according to IEC 60068-2-27                        | sinusoidal half-wave 15g / 11 ms                |
| vibration resistance                               |   |
| according to IEC 60068-2-6                         | 10 500 Hz: 5g                                   |
| operating frequency maximum                        | 1 800 1/h                                       |
| mechanical service life (operating cycles) typical | 500 000   |
| reference code according to IEC 81346-2            | S   |
| Substance Prohibitance (Date)                      | 10/01/2014                                      |
| Ambient conditions                                 |   |
| ambient temperature                                |   |
| <ul> <li>during operation</li> </ul>               | -25 +70 °C                                      |
| during storage                                     | -40 +80 °C                                      |

| environmental category during operation according to | IEC |
|--|-----|
| 60721  |     |

3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%)

| Installation/ mounting/ dimensions          |         |  |
|---|---------|--|
| height                                      | 40 mm   |  |
| width                                       | 40 mm   |  |
| shape of the installation opening           | round   |  |
| mounting diameter                           | 22.3 mm |  |
| positive tolerance of installation diameter | 0.4 mm  |  |
| mounting height                             | 27.5 mm |  |
| installation width                          | 40 mm   |  |
| installation depth                          | 24.4 mm |  |
| Certificates/ approvals                     |         |  |
| Fundle on the former efforts                |         |  |

## Further information

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1050-1BA10-0AA0-Z Y12

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1050-1BA10-0AA0-Z Y12

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1050-1BA10-0AA0-Z Y12

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=3SU1050-1BA10-0AA0-Z Y12&lang=en

last modified:

1/27/2022 🖸