SIEMENS

Data sheet



Illuminated mushroom pushbutton, 22 mm, round, metal, shiny, yellow, 30 mm, latching, pull-to-unlatch mechanism, Z=50-unit packaging

product brand name	SIRIUS ACT
product designation	Mushroom pushbuttons
design of the product	Actuating/signaling element
product type designation	3SU1
product line	Metal, shiny, 22 mm
Enclosure	
number of command points	1
Actuator	
design of the actuating element	illuminated
principle of operation of the actuating element	latching
product extension optional light source	Yes
color of the actuating element	yellow
material of the actuating element	plastic
shape of the actuating element	round
outer diameter of the actuating element	30 mm
type of unlocking device	pull-to-unlatch mechanism
number of switching positions	2
Front ring	
product component front ring	Yes
design of the front ring	Standard
material of the front ring	Metal, high gloss
color of the front ring	silver
General technical data	
product function	
 EMERGENCY OFF function 	No
EMERGENCY STOP function	No
protection class IP	IP66, IP67, IP69(IP69K)
degree of protection NEMA rating	1, 2, 3, 3R, 4, 4X, 12, 13
shock resistance	
according to IEC 60068-2-27	sinusoidal half-wave 15g / 11 ms
vibration resistance	
according to IEC 60068-2-6	10 500 Hz: 5g
operating frequency maximum	1 800 1/h
mechanical service life (operating cycles) typical	500 000
reference code according to IEC 81346-2	\$
Substance Prohibitance (Date)	10/01/2014
Ambient conditions	
ambient temperature	
during operation	-25 +70 °C
during storage	-40 +80 °C

environmental category during operation according to IEC 60721	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%)	
Installation/ mounting/ dimensions		
height	30 mm	
width	30 mm	
shape of the installation opening	round	
mounting diameter	22.3 mm	
positive tolerance of installation diameter	0.4 mm	
mounting height	27.5 mm	
installation width	30 mm	
installation depth	24.4 mm	
Certificates/ approvals		
Further information		

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1051-1AA30-0AA0-Z X90

Cax online generator


 $\underline{http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en\&mlfb=3SU1051-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-0AA0-Z~X90-1AA30-2AA0-Z~X90-1AA30-2AA0-Z~X90-1AA30-2AA0-Z~X90-1AA30-2AA0-Z~X90-1AA30-2AA0-Z~X90-2AA0-Z~X90-2AA0-Z~X90-2AA0-Z~X90-2AA0-Z~X90-2AA0-Z~X90-2AA0-Z~X90-2AA0-Z~X90-2AA0-Z~X90-2AA0-Z~X90-2AA0-Z~X90-2AA0-Z~X90-2AA0-Z~X90-2AA0-Z~X90-2AA0-Z~X90-2AA0-Z~X90-2AA0-Z~X90-2AA0-Z~X90-2AA$


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1051-1AA30-0AA0-Z X90

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1051-1AA30-0AA0-Z X90&lang=en





last modified: 1/27/2022 🖸