9001KM7LR

30mm Push Button, Types K, SK or KX, light module, red LED lamp, 220/240 VAC 50/60 Hz



Main		
Range of Product	Harmony 9001K Harmony 9001SK	
Product or Component Type	Light module Light block	
Device short name	9001K	
Bulb base	BA 9s	
Light block supply	Direct via integral transformer	

Complementary

Light source	LED (bulb included)
Light block colour	Red
[Us] rated supply voltage	240 V AC 60 Hz
	220 V AC 50 Hz

Environment

Liviloiiiieiit		
Protective treatment	TC	
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	
	-4070 °C (-40158 °F)	
Ambient Air Temperature for Operation	-13158 °F (-2570 °C)	
	-2570 °C (-13158 °F)	
IP degree of protection	IP20 IEC 60529	
Standards	UL 508	
	CSA C22.2 No 14	
	EN/IEC 60947-5-4	
	EN/IEC 60947-5-1	
	EN/IEC 60947-1	
	JIS C 4520	
	JIS C 852	
Product Certifications	UL Listed[RETURN]CSA[RETURN]NEMA	
Electrical shock protection class	Class II IEC 61140	
Vibration resistance	7 gn 2500 Hz)IEC 60068-2-6	
Shock resistance	50 gn IEC 60068-2-27	

Ordering and shipping details

US10CS121435	
0CS1	
785901877127	
No	
MX	
	0CS1 785901877127 No

Packing Units

PCE	
1	
5.080 in (12.903 cm)	
2.0000000000 in (5.08 cm)	
12.903 in (32.774 cm)	
4.00 oz (113.398 g)	
	1 5.080 in (12.903 cm) 2.0000000000 in (5.08 cm) 12.903 in (32.774 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months