8903SMG1V02

Contactor, Type S, multipole lighting, electrically held, 30A, 2 pole, 110/120VAC 50/60Hz coil, NEMA 1



Main

Product	Electrically Held Lighting Contactor
Туре	S

Complementary

Complementary		
Control Circuit Voltage	120 V AC 60 Hz	
	110 V AC 50 Hz	
Current Rating	30 A	
Number of Poles	2P	
Control Units	No control units	
Pilot Light	Without pilot light	
Auxiliary Contacts	Without	
Other Options	None	
Electrical Connection	Lugs	
Height	10.00 in (254 mm)	
Depth	5.28 in (134 mm)	
Width	5.98 in (152 mm)	
	• • •	

Environment

Enclosure Type	NEMA 1 painted sheet steel surface none
Product Certifications	UL Listed[RETURN]CSA

Ordering and shipping details

Category	US10CP121325	
Discount Schedule	0CP1	
GTIN	785901619581	
Returnability	No	
Country of origin	US	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	6.00 in (15.24 cm)	
Package 1 Width	6.50 in (16.51 cm)	
Package 1 Length	11.50 in (29.21 cm)	
Package 1 Weight	6.44 lb(US) (2.921 kg)	
Unit Type of Package 2	PAL	
Number of Units in Package 2	120	

Package 2 Height	40.00 in (101.6 cm)
Package 2 Width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	845.76 lb(US) (383.63 kg)

Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Not compliant	
China RoHS Regulation	China RoHS Declaration	

Contractual warranty

Warranty	18 months