8903SQG1V02

Contactor, Type S, multipole lighting, electrically held, 100A, 2 pole, 110/120VAC 50/60Hz coil, NEMA 1



Main

Product	Electrically Held Lighting Contactor	
Туре	S	

Complementary

Complementary		
Control Circuit Voltage	120 V AC 60 Hz	
	110 V AC 50 Hz	
Current Rating	100 A	
Number of Poles	2P	
Control Units	No control units	
Pilot Light	Without pilot light	
Auxiliary Contacts	Without	
Other Options	None	
Electrical Connection	Lugs	
Height	25.16 in (639 mm)	
Depth	8.98 in (228 mm)	
Width	11.26 in (286 mm)	

Environment

Enclosure Type	NEMA 1 painted sheet steel surface none
Product Certifications	UL Listed[RETURN]CSA

Ordering and shipping details

Category	US10CP121325
Discount Schedule	0CP1
GTIN	785901619444
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	10.60 in (26.924 cm)	
Package 1 Width	12.00 in (30.48 cm)	
Package 1 Length	25.70 in (65.278 cm)	
Package 1 Weight	34.37 lb(US) (15.59 kg)	

Offer Sustainability

REACh Regulation	REACh Declaration	
EU RoHS Directive	Not compliant	
China RoHS Regulation	China RoHS Declaration	

Contractual warranty

We would be		
Warranty	19 months	
	10 1110111115	