

## 8903SVO1V02

Contactor, Type S, multipole lighting,  
electrically held, 200A, 2 pole, 110/120VAC  
50/60Hz coil, open style



### Main

Product	Electrically Held Lighting Contactor
Type	S

### Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	200 A
Number of Poles	2P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical Connection	Lugs
Height	9.13 in (232 mm)
Depth	6.50 in (165 mm)
Width	5.98 in (152 mm)

### Environment

Enclosure Type	Not rated (open device) surface none
Product Certifications	UL Listed[RETURN]CSA


### Ordering and shipping details

Category	US10CP121325
Discount Schedule	0CP1
GTIN	785901626015
Returnability	No
Country of origin	MX

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.80 in (19.812 cm)
Package 1 Width	8.80 in (22.352 cm)
Package 1 Length	14.40 in (36.576 cm)
Package 1 Weight	17.00 lb(US) (7.711 kg)

Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#"> REACH Declaration</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	<a href="#"> China RoHS Declaration</a>

Contractual warranty

Warranty	18 months
----------	-----------