

# LC1G400KUEN

Contactor, high power, TeSys Giga, standard version, 3 pole/NO, AC-3  $\leq 440\text{V}$  400A, 100-250VAC/DC coil



## Main

Range	TeSys
Range of Product	TeSys Giga
Product or Component Type	Contacteur
Device short name	LC1G
Contactor application	Power switching Motor control
Utilisation category	AC-1 AC-3 AC-3e AC-4 AC-5a AC-5b AC-6a AC-6b AC-8a AC-8b DC-1 DC-3 DC-5
Poles description	3P
[Ue] rated operational voltage	$\leq 1000\text{ V AC } 50/60\text{ Hz}$ $\leq 460\text{ V DC}$
[Ie] rated operational current	550 A (at $<104\text{ }^\circ\text{F}$ ( $40\text{ }^\circ\text{C}$ )) at $\leq 1000\text{ V AC-1}$ 400 A (at $<140\text{ }^\circ\text{F}$ ( $60\text{ }^\circ\text{C}$ )) at $\leq 440\text{ V AC-3}$
[Uc] control circuit voltage	100...250 V AC 50/60 Hz 100...250 V DC
Control circuit voltage limits	Operational: 0.8 Uc Min...1.1 Uc Max (at $<140\text{ }^\circ\text{F}$ ( $60\text{ }^\circ\text{C}$ )) Drop-out: 0.1 Uc Max...0.45 Uc Min (at $<140\text{ }^\circ\text{F}$ ( $60\text{ }^\circ\text{C}$ ))

## Complementary

[Uimp] rated impulse withstand voltage	8 kV
Overtoltage category	III
[Ith] conventional free air thermal current	550 A (at $104\text{ }^\circ\text{F}$ ( $40\text{ }^\circ\text{C}$ ))
Rated breaking capacity	3480 A at 440 V
[Icw] rated short-time withstand current	3.6 KA - 10 s 2.4 KA - 30 s 1.7 KA - 1 min 1.2 KA - 3 min 1.0 KA - 10 min
Associated fuse rating	500 A aM at $\leq 440\text{ V}$ for motor 315 A aM at $\leq 690\text{ V}$ for motor 630 A gG at $\leq 690\text{ V}$
Average impedance	0.0001 Ohm
[Ui] rated insulation voltage	1000 V
Power dissipation per pole	30 W AC-1 - Ith 550 A 16 W AC-3 - Ith 400 A
Compatibility code	LC1G
Pole contact composition	3 NO
Auxiliary contact composition	1 NO + 1 NC

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Motor power kW	110 KW at 230 V AC 50/60 Hz (AC-3e) 200 KW at 400 V AC 50/60 Hz (AC-3e) 200 KW at 415 V AC 50/60 Hz (AC-3e) 250 KW at 440 V AC 50/60 Hz (AC-3e) 250 KW at 500 V AC 50/60 Hz (AC-3e) 315 KW at 690 V AC 50/60 Hz (AC-3e) 220 KW at 1000 V AC 50/60 Hz (AC-3e) 110 KW at 230 V AC 50/60 Hz (AC-3) 200 KW at 400 V AC 50/60 Hz (AC-3) 200 KW at 415 V AC 50/60 Hz (AC-3) 250 KW at 440 V AC 50/60 Hz (AC-3) 250 KW at 500 V AC 50/60 Hz (AC-3) 315 KW at 690 V AC 50/60 Hz (AC-3) 220 KW at 1000 V AC 50/60 Hz (AC-3) 110 KW at 230 V AC 50/60 Hz (AC-4) 200 KW at 400 V AC 50/60 Hz (AC-4) 200 KW at 415 V AC 50/60 Hz (AC-4) 220 KW at 440 V AC 50/60 Hz (AC-4) 250 KW at 500 V AC 50/60 Hz (AC-4) 315 KW at 690 V AC 50/60 Hz (AC-4) 220 kW at 1000 V AC 50/60 Hz (AC-4)
Maximum Horse Power Rating	125 Hp at 200/208 V 60 Hz 150 Hp at 230/240 V 60 Hz 300 Hp at 460/480 V 60 Hz 400 hp at 575/600 V 60 Hz
Irms rated making capacity	5090 A at 440 V
Coil technology	Built-in bidirectional peak limiting
Mechanical durability	8 Mcycles
Inrush power in VA (50/60 Hz, AC)	750 VA
Inrush power in W (DC)	660 W
Hold-in power consumption in VA (50/60 Hz, AC)	15.5 VA
Hold-in power consumption in W (DC)	9.3 W
Operating time	40...70 ms closing 15...50 ms opening
Maximum operating rate	600 Cyc/H AC-3 600 Cyc/H AC-3e 300 Cyc/H AC-1 150 cyc/h AC-4
Connections - terminals	Power circuit: bar 2 - busbar cross section: 32 x 10 mm Power circuit: lugs-ring terminals 1 0.29 in <sup>2</sup> (185 mm <sup>2</sup> ) Power circuit: bolted connection Control circuit: push-in 1 0.00...0.00 in <sup>2</sup> (0.2...2.5 mm <sup>2</sup> ) - cable stiffness: solid stranded without cable end Control circuit: push-in 1 0.00...0.00 in <sup>2</sup> (0.25...2.5 mm <sup>2</sup> ) - cable stiffness: flexible with cable end Control circuit: push-in 2 0.00...0.00 in <sup>2</sup> (0.5...1.0 mm <sup>2</sup> ) with cable end Control circuit: push-in 0.00...0.00 in <sup>2</sup> (0.75...2.5 mm <sup>2</sup> ) - cable stiffness: solid stranded without cable end Control circuit: push-in 0.00...0.00 in <sup>2</sup> (0.75...2.5 mm <sup>2</sup> ) - cable stiffness: flexible with cable end
Connection pitch	1.77 in (45 mm)
Mounting Support	Plate
Standards	EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 CSA C22.2 No 60947-4-1 JIS C8201-4-1 JIS C8201-5-1
Product Certifications	CB Scheme[RETURN]CCC[RETURN]cULus[RETURN]EAC[RETURN]CE[RETURN]UKCA[RETURN] RO-MR by DNV-GL
Tightening torque	309.78 lbf.in (35 N.m)
Height	8.86 in (225 mm)
Width	5.51 in (140 mm)
Depth	8.90 in (226 mm)
Net Weight	16.53 lb(US) (7.5 kg)

## Environment

IP degree of protection	IP2X front face with shrouds IEC 60529 IP2X front face with shrouds VDE 0106
Ambient air temperature for operation	-13...140 °F (-25...60 °C)
Ambient Air Temperature for Storage	-76...176 °F (-60...80 °C)
Mechanical robustness	Vibrations 5...300 Hz 2 gn contactor open Vibrations 5...300 Hz 4 gn contactor closed Shocks 10 gn 11 ms contactor open Shocks 15 gn 11 ms contactor closed
Color	Dark grey
Protective treatment	TH
Permissible ambient air temperature around the device	-40...158 °F (-40...70 °C) at Uc

## Ordering and shipping details

Category	US10I1222329
Discount Schedule	0I12
GTIN	3606481921987
Returnability	Yes
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12.20 in (31.000 cm)
Package 1 Width	12.20 in (31.000 cm)
Package 1 Length	8.86 in (22.500 cm)
Package 1 Weight	17.03 lb(US) (7.726 kg)
Unit Type of Package 2	P06
Number of Units in Package 2	4
Package 2 Height	29.53 in (75.000 cm)
Package 2 Width	23.62 in (60.000 cm)
Package 2 Length	31.50 in (80.000 cm)
Package 2 Weight	92.38 lb(US) (41.904 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
PVC free	Yes
Halogen content performance	Halogen free plastic parts product