P30P47A12P1-120 Pending obsolescence

Potter & Brumfield | Potter & Brumfield P30

TE Internal #: 3-1393132-8

TE Internal Description: P30P47A12P1-120=CONTACTORS

View on TE.com >



Relays & Contactors > Contactors > Definite Purpose Contactors











Number of Poles: 4

Coil Voltage Rating: 120 VAC Contact Current Rating: 30 A

Contact Arrangement: 4 Form X, 4PST-NO-DM

Coil Resistance: 117 Ω

Features

Configuration Features

| Auxiliary Switch Contact Arrangement | Without |
|--------------------------------------|----------------------|
| Number of Poles | 4 |
| Contact Arrangement | 4 Form X, 4PST-NO-DM |
| | |

Electrical Characteristics

| Contact Switching Voltage (Max) | 600 VAC |
|---------------------------------|---------|
| Coil Voltage Rating | 120 VAC |
| Contact Current Rating | 30 A |
| Coil Resistance | 117 Ω |

Contact Features

| Contact Material | Silver Cadmium Oxide |
|------------------|----------------------|
| | |

Termination Features

| Mains Termination & Connection Type | Screw Terminal |
|-------------------------------------|-----------------------------------|
| Coil Termination & Connection Type | 8-32 Screw with .25 Quick Connect |

Mechanical Attachment

| Product Mount Type Chassis | |
|----------------------------|--|
|----------------------------|--|



Operation/Application

| Actuating System AC | |
|---------------------|--|
|---------------------|--|

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant with Exemptions |
|---|--|
| EU ELV Directive 2000/53/EC | Not Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JUNE 2022 (224) SVHC > Threshold: Cadmium oxide (10.81% in Component Part) Article Safe Usage Statements: Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. |
| Halogen Content | Not Yet Reviewed for halogen content |
| Solder Process Capability | Not applicable for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts







Also in the Series

Customers Also Bought













Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_3-1393132-8_D.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_3-1393132-8_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_3-1393132-8_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use.

Datasheets & Catalog Pages

P30/P40 Definite Purpose Magnetic Contactor 30/40 Ampere Full Load 40/50 Ampere Resistive AC & DC Coils

English

Product Specifications

Definitions General Purpose Relays

English