FA Integrated Tool Package CX-One CX-One Ver.4

Greater Integration with the CX-One

• The CX-One is a comprehensive software package that integrates PLC Programming Software with Support Software for setting up Networks, Programmable Terminals, Servo Systems, Inverters, and Temperature Controllers.



Features

- Integrated Software Management for OMRON PLCs and Components
- CPU Bus Units and Special I/O Units can be set without concern for memory addresses and without relying on operation manuals
- Support Software for CPU Bus Units and Special I/O Units can be started from the I/O tables
- Integrated Simulation for Greater Design and Debugging Efficiency
- Online Web Services

Microsoft, Visual Basic, Visual C#, Visual Studio, Windows and Windows Vista are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

DeviceNet, DeviceNet Safety, CompoNet, and EtherNet/IP are either registered trademarks or trademarks of ODVA.

Other company names and product names in this document are the trademarks or registered trademarks of their respective companies.

Ordering Information

Product name	Specifications			Model	Standards
FIGUUCI name	Specifications	Number of licenses	Media	woder	Stanuarus
FA Integrated Tool Package CX-One	The CX-One is a comprehensive software package that integrates Support Software for OMRON PLCs and components.	– (Media only) *3	DVD	CXONE-AL00D-V4	-
		1 license		CXONE-AL01D-V4	
		3 licenses		CXONE-AL03D-V4	
		10 licenses		CXONE-AL10D-V4	
	CX-One runs on the following OS. Windows 7 (32-bit/64-bit version) *1 / Windows 8.1 (32-bit/64-bit	30 licenses		CXONE-AL30D-V4	
	version) *2 / Windows 10 (32-bit/64-bit version) / Windows 11	50 licenses		CXONE-AL50D-V4	
	(64-bit version)	Unrestricted *4 (Site license)		Ask your OMRON representative for details.	
Ver.4.	The upgrade versions *5	1 license	DVD	CXONE-AL01D-V4-UP	-
		3 licenses		CXONE-AL03D-V4-UP	
		10 licenses		CXONE-AL10D-V4-UP	
		30 licenses		CXONE-AL30D-V4-UP	
		50 licenses		CXONE-AL50D-V4-UP	
		Unrestricted *4 (Site license)		CXONE-ALXXD-V4-UP	
FA Integrated Tool Package CX-One Lite Ver.4.⊡	CX-One Lite is a subset of the complete CX-One package that provides only the Support Software required for micro PLC applications. CX-One Lite runs on the following OS.	1 license	DVD	CXONE-LT01D-V4	_
	Windows 7 (32-bit/64-bit version) *1 / Windows 8.1 (32-bit/64-bit version) *2 / Windows 10 (32-bit/64-bit version) / Windows 11 (64-bit version)				
	The upgrade versions *5	1 license	DVD	CXONE-LT01D-V4-UP	-

Note: The CX-One and CX-One Lite cannot be simultaneously installed on the same computer.

*1. Windows 7 Service Pack1 (KB976932) must be applied.

Windows 7 Update (KB4474419 and KB4490628) must be applied to use the auto-update system.

***2.** Windows 8.1 Update (KB2919355) must be applied.

***3.** The CXONE-AL00D-V4 contains only the DVD installation media for users who have purchased the CX-One Version 4. □ and does not include the license number. Enter the license number of the CX-One Version 4. □ when installing. (The license number of the CX-One Version 3. □ or lower cannot be used for installation.)

***4.** This is a site license for users who want to use CX-One on many computers.

•The number of users is unrestricted for the same company and site.

•Only one license number must be managed.

•All computers that use the site license can take advantage of automatic updates and software downloads.

***5.** The upgrade versions are for customers that already have CX-One Version 3.□ or lower.

Product Configuration

Setup disk: (DVD) DVD 1 piece in the case Guidance: A4 size, English/Japanese Product Registration Guide, Japanese

User license agreement/User registration card,English/Japanese

Support Software

The following tables lists the Support Software that can be installed from CX-One

Support Software in CX-One	Outline		
CX-Programmer	Application software to create and debug programs for CS/CJ/CP/NSJ-series, C-series, and CVM1/CV-series CPU Units. Data can be created and monitored for high-speed-type Position Control Units.		
CX-Integrator	Application software to build and set up FA networks, such as Controller Link, DeviceNet, CompoNet, CompoWay, and Ethernet networks. The Routing Table Component and Data Link Component can be started from here. DeviceNet Configuration functionality is also included.		
Switch Box Utility	Utility software that helps you to debug PLCs. It helps you to monitor the I/O status and to monitor/change present values within the PLC you specify.		
CX-Protocol	Application software to create protocols (communications sequences) between CS/CJ/CP/NSJ-series or C200HX/HG/ HE Serial Communications Boards/Units and general-purpose external devices.		
CX-Simulator	Application software to simulate CS/CJ/CP/NSJ-series CPU Unit operation on the computer to debug PLC programs without a CPU Unit.		
CX-Position	Application software to create and monitor data for CS/CJ-series Position Control Units (except for High-speed type).		
CX-Motion-NCF	Application software to monitor and set parameters for CS/CJ-series Position Control Units and Servo Drivers that support MECHATROLINK-II communications.		
CX-Motion-MCH	Application software to create data for CS/CJ-series MCH Units, create motion programs, and perform monitoring.		
CX-Motion	Application software to create data for CS/CJ-series, C200HX/HG/HE, and CVM1/CV-series Motion Control Units, and to create and monitor motion control programs.		
CX-Drive	Application software to set and control data for Inverters and Servos.		
CX-Process Tool	Application software to create and debug function block programs for CS/CJ-series Loop Controllers (Loop Control Units/Boards, Process Control CPU Units, and Loop Control CPU Units).		
Faceplate Auto-Builder for NS	Application software that automatically outputs screen data as project files for NS-series PTs from tag information in function block programs created with the CX-Process Tool.		
CX-Designer	Application software to create screen data for NS-series PTs.		
NV-Designer	Application software to create screen data for NV-series small PTs.		
CX-ConfiguratorFDT	Application software for setting various units by installing its DTM module.		
CX-Thermo	Application software to set and control parameters in components such as Temperature Control Units.		
CX-FLnet	Application software for system setting and monitoring of CS/CJ-series FI-net Units.		
Network Configurator	Application software to setup and monitor tag data Link for CJ2 (Built-in EtherNet/IP) CPU Units and EtherNet/IP Units.		
NX-IO Configurator	Application software to set up and maintain EtherNet/IP Coupler Units and NX-series I/O Units on an EtherNet/IP Coupler Unit.		
CX-Server	Middleware necessary for CX-One applications to communicate with OMRON components, such as PLCs, Display Devices, and Temperature Control Units.		
Communications Middleware	Middleware necessary to communicate with CP1/CP2 CPU Units with built-in Ethernet port and to use secure communication with CS/CJ CPU Units.		
PLC Tools	A group of components used with CX-One applications, such as the CX-Programmer and CX-Integrator. Includes the following: I/O tables, PLC memory, PLC Setup, Data Tracing/Time Chart Monitoring, PLC Error Logs, File Memory, PLC clock, Routing Tables, and Data Link Tables.		

System Requirements

(32-bit/64-bit version) *3 / Windows 8.1 (32-bit/64-bit version) *4 / Windows 10 (32-bit/64-bit version) / 1 (64-bit version) r recommended by Microsoft	
r recommended by Microsoft	
recommended by Microsoft	
Approx. 4.0 GB or more available space is required to install the complete CX-One package.	
XGA (1,024 × 768), High-Color 16-bit min.	
drive	
ort, USB port, or Ethernet port *6	

***1.** CX-One Operating System Precaution

1) System requirements and hard disk space may vary with the system environment.

*2. The applications listed in the table below have restrictions.

Application	Restriction	
CX-Designer/ NV-Designer	If a new font (e.g., Meiryo) of Windows 7 or later OS is used in a project, the font size on labels may be bigger and protrude from the components if the project is transferred from CX-Designer running on a Windows XP or earlier OS to the NS/NSJ.	
CX-Programmer/ CX-Integrator/ Network Configurator	Although you can install CPS files, EDS files, Expansion Modules, and Interface Modules, the virtual store function of Windows OS imposes the following restrictions on the use of the software after installation. These restrictions will not exist if application data is installed using Run as Administrator. • If another user logs in, the applications data will need to be installed again. • The CPS files will not be automatically updated.	
CX-ConfiguratorFDT	.NET Framework 4.8 is required when CX-ConfiguratorFDT Ver.3 is used.	
CX-Server	 Restrictions are imposed on the following functions. The driver cannot be changed from the default setting if Controller Link is set as the network type in the Change PLC dialog box. Online connections will not be possible through Controller Link Boards or SYSMAC LINK Boards. Online connections using FinsGateway as the network type will not be possible from the CX-Programmer or CX-Integrator. Communications will not be possible though a CS1 Board and PCI bus. 	

*3. Windows 7 Service Pack1 (KB976932) must be applied.

Windows 7 Update (KB4474419 and KB4490628) must be applied to use the auto-update system.

***4.** Windows 8.1 Update (KB2919355) must be applied.

*5. The amount of memory required varies with the Support Software used in CX-One for the following Support Software. Refer to user documentation for individual Support Software for details. CX-Programmer, CX-Designer, CX-Thermo, CX-Simulator, CX-Protocol, CX-Motion, CX-Drive, CX-Process Tool, and Faceplate Auto-Builder

for NS ***6.** Refer to the hardware manual for your PLC for hardware connection methods and cables to connect the computer and PLC.

Hard Disk Space Requirements

Support Software in CX-One	Approx. hard disk space required.	Remarks	
CX-Programmer	Approx. 330 MB		
CX-Position	Approx. 15 MB		
CX-Motoion	Approx. 45 MB		
CX-Motion-NCF	Approx. 260 MB		
CX-Motion-MCH	Approx. 60 MB		
CX-Drive	Approx. 200 MB		
NV-Designer	Approx. 150 MB	Options can be selected or cleared to install or not	
CX-Process Tool	Approx. 100 MB	install individual Support Sofftware.	
Faceplate Auto-Builder for NS	Approx. 70 MB		
CX-Simulator	Approx. 45 MB		
CX-Thermo	Approx. 200 MB		
CX-Finet	Approx. 2 MB		
Switch Box Utility	Approx. 5 MB		
NX-IO Configurator	Approx. 120 MB		
CX-Integrator	Approx. 260 MB		
CX-Designer	Approx. 750 MB		
CX-Protocol	Approx. 20 MB	Alwaya installed *	
Network Configurator	Approx. 40 MB	Always installed. *	
CX-ConfiguratorFDT	Approx. 60 MB	1	
CX-Server, Communications Middleware and PLC To	Approx. 750 MB		

* The CX-Server, Communications Middleware and PLC Tools (common components) are installed on the system drive.

Note: If the complete CX-One package is installed, approximately 4.0 GB of hard disk space will be required (including workspace required for installation). Check available space on your hard disk before installing software.

Related Manuals

Cat. No.	Model	Manual name	Contents
W463	CXONE-AL D-V4	CX-One Setup Manual	Installation and overview of CX-One FA Integrated Tool Package.

OMRON

OMRON AUTOMATION AMERICAS HEADQUARTERS • Chicago, IL USA • 847.843.7900 • 800.556.6766 • automation.omron.com

OMRON CANADA, INC. • HEAD OFFICE Toronto, ON, Canada • 416.286.6465 • 866.986.6766 • automation.omron.com

OMRON ELECTRONICS DE MEXICO • HEAD OFFICE Ciudad de México • 52.55.5901.4300 • 01.800.386.6766 • mela@omron.com

OMRON ELECTRONICS DE MEXICO • SALES OFFICE San Pedro Garza García, N.L. • 81.12.53.7392 • 01.800.386.6766 • mela@omron.com

OMRON ELECTRONICS DE MEXICO • SALES OFFICE Eugenio Garza Sada,León, Gto • 01.800.386.6766 • mela@omron.com OMRON ELETRÔNICA DO BRASIL LTDA • HEAD OFFICE São Paulo, SP, Brasil • 55 11 5171-8920 • automation.omron.com

OMRON ARGENTINA • SALES OFFICE Buenos Aires, Argentina • +54.11.4521.8630 • +54.11.4523.8483 mela@omron.com

OTHER OMRON LATIN AMERICA SALES +54.11.4521.8630 • +54.11.4523.8483 • mela@omron.com

Authorized Distributor:

Controllers & I/O

Machine Automation Controllers (MAC)
 Motion Controllers

Programmable Logic Controllers (PLC)
 Temperature Controllers
 Remote I/O

Robotics

Industrial Robots
 Mobile Robots

Operator Interfaces

• Human Machine Interface (HMI)

Motion & Drives

- Machine Automation Controllers (MAC)
 Motion Controllers
 Servo Systems
- Frequency Inverters

Vision, Measurement & Identification

Vision Sensors & Systems
 Measurement Sensors
 Auto Identification Systems

Sensing

- Photoelectric Sensors Fiber-Optic Sensors Proximity Sensors
- Rotary Encoders
 Ultrasonic Sensors

Safety

- Safety Light Curtains
 Safety Laser Scanners
 Programmable Safety Systems
- Safety Mats and Edges Safety Door Switches Emergency Stop Devices
- Safety Switches & Operator Controls Safety Monitoring/Force-guided Relays

Control Components

- Power Supplies
 Timers
 Counters
 Programmable Relays
- Digital Panel Meters
 Monitoring Products

Switches & Relays

- Limit Switches Pushbutton Switches Electromechanical Relays
- Solid State Relays

Software

Programming & Configuration • Runtime