




Ceramic SMD Crystals 3225SX Series

Model C7

4 PADS 3.2 X 2.5



Frequency Range : 8.00MHz to 150.00MHz

Features :

- High reliability & low cost unit
- Tight stability & extended temperature available
- Lead-free type
- For automotive applications, please contact our sales representatives

QUARTZ
CRYSTALS





Standard Specifications

Item	Value	
Frequency Range	8.00MHz to 150.00MHz	
Frequency Tolerance	±10ppm, ±20ppm (or specify)	
Frequency Tolerance over Temperature range	±10ppm	±20ppm
Operating Temperature Range	-20°C to + 75°C	-40°C to +85°C
Operable Temperature Range	-40°C to +90°C	
Drive Level	50uW Typ (100uW Max)	
Load Capacitance	8pF (or specify)	


ESR Table

Frequency Range (MHz)	Standard ESR (Ohm)
8.00 ~ 9.99	500
10.00 ~ 11.99	300
12.00 ~ 12.99	200
13.00 ~ 15.99	150
16.00 ~ 19.99	80
20.00 ~ 21.99	60
22.00 ~ 54.00	50
60.00 ~ 150.00 (30/T)	300

Dimension



Soldering Pattern



Note:

1. Manufacturer reserves the right to change the specification and content of this product for improvement without notification.
2. Custom specification is welcome. Please contact our sales representative for further details.
3. If the crystal is intended for applications which have direct impact on human life and properties, and require a high degree of reliability and safety concerns, customers must provide full information such as but not limit to the application, electrical and reliability specification at the inquiry beginning stage.
4. Customers have to agree to the "Guideline for handling crystal units" and "Standard Terms and Condition of Sales" which is printed this catalog before placing orders to our company or our distributors. There are also unpredictable factors such as applied condition, oscillation margin and etc and customers must check them beforehand. In case of queries, please do not fail to send inquiry to our company before ordering.

Ver 1.2

