

Null Modem Serial DB9 Serial Cable (DB9 F/F), 6 ft. (1.83 m)

MODEL NUMBER: **P450-006**



Highlights

- Superior molded cables with integral strain relief and foil-shielding for maximum EMI/RFI protection
- Gold-plated connectors provide superior conductivity
- Null modem cables connect two serial devices that require a null modem configuration

System Requirements

- Two serial devices with DB9M connectors requiring a null modem (cross-wired) configuration

Package Includes

- 6-ft. (1.83 m) Null Modem Gold Cable DB9F to DB9F

Description

Null modem cables and adapters connect two serial devices that require a null modem (cross-wired) configuration. This 6-ft. (1.83 m) cable has a DB9 female connector on each end. Superior molded cables with foil-shielding offer maximum EMI/RFI protection. Gold-plated connectors and contacts provide superior conductivity.

Features

- DB9 female to DB9 female, 6-ft. (1.83 m)
- Full Handshake Null wiring configuration: 1+6 - 4, 2-3, 3-2, 4 - 1+6, 5-5, 7-8, 8-7.
- Superior molded cables with foil-shielding for maximum EMI/RFI protection
- Gold-plated connectors provide superior conductivity

Specifications

OVERVIEW	
UPC Code	037332013323
CONNECTIONS	
Side A - Connector 1	DB9 (FEMALE)
Side B - Connector 1	DB9 (FEMALE)
PHYSICAL	
Color	Black
Cable Jacket Color	Black
Cable Length (ft.)	6

Cable Length (m)	1.83
Shipping Dimensions (hwd / in.)	8.50 x 6.90 x 0.50
Shipping Dimensions (hwd / cm)	21.59 x 17.53 x 1.27
Shipping Weight (lbs.)	0.26
Shipping Weight (kg)	0.12
STANDARDS & COMPLIANCE	
Product Compliance	RoHS
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty

1000 Eaton Boulevard
Cleveland, OH 44122
United States
<https://tripplite.eaton.com>

© 2024 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.