



Connectors > Connector Accessories > Connector Hardware > Double Sided QLPIN Bulkhead



Hardware Accessory Function: **Latching, Locking & Retention**

Connector Hardware Accessory Type: **Quick Lock Pins**

Operating Temperature (Max): **90 °C [ 194 °F ]**

Operating Temperature Range: **-40 - 90 °C [ -40 - 194 °F ]**

[All Double Sided QLPIN Bulkhead \(6\)](#)

Features

Product Type Features

|                                   |                               |
|-----------------------------------|-------------------------------|
| Hardware Accessory Function       | Latching, Locking & Retention |
| Connector Hardware Accessory Type | Quick Lock Pins               |

Mechanical Attachment

|             |      |
|-------------|------|
| Thread Size | None |
|-------------|------|

Usage Conditions

|                             |                           |
|-----------------------------|---------------------------|
| Operating Temperature (Max) | 90 °C[194 °F]             |
| Operating Temperature Range | -40 - 90 °C[-40 - 194 °F] |

Packaging Features

|                    |     |
|--------------------|-----|
| Packaging Quantity | 500 |
| Packaging Method   | Box |

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

|   |   |
|---|---|
| EU RoHS Directive 2011/65/EU                  | Compliant with Exemptions                   |
| EU ELV Directive 2000/53/EC                   | Not Yet Reviewed                            |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold        |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JAN 2024 (240) |



Candidate List Declared Against: JAN 2024  
(240)  
SVHC > Threshold:  
Pb (.35% in Component Part)

**Article Safe Usage Statements:**  
Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

|                           |   |
|---------------------------|---|
| Halogen Content           | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Not reviewed for solder process capability  |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # CAT-R131-D743  
Double Sided QLPIN Bulkhead

Also in the Series | Rail D-Sub Backshells

Connector Backshells(55)

Connector Contacts(5)

Connector Hardware(19)

Connector Strain Relief(67)



Crimp D-Sub Connectors(10)



Insertion & Extraction Tools(2)

Customers Also Bought



TE Part # DT04-2P  
REC, 2P, GRY, N



TE Part # DT06-2S  
PLG, 2P, GRY, N




TE Part # W2S  
Wedgelocks: DEUTSCH DT



TE Part # 0460-202-16141  
DEUTSCH Solid Contacts



TE Part # 282104-1  
AMP SUPERSEAL 1.5MM,  
CONNECTOR HOUSING



TE Part # 281934-2  
SINGLE WIRE SEAL



TE Part # 114017-ZZ  
SEALING PLUG, SIZE 12/16, WHT

Documents

Product Drawings

QL-SET FOR VAR. E LATCH PIN WITH GUIDE 5

English

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_1-2308298-5\_A.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_1-2308298-5\_A.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_1-2308298-5\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.



---

Datasheets & Catalog Pages

Rail D-Sub Backshells Flyer

English