

InduCom9 9p 2T-entry hexscrew M3




Image is for illustration purposes only. Please refer to product description.

Part number	66 67 009 0347
Specification	InduCom9 9p 2T-entry hexscrew M3
HARTING eCatalogue	https://b2b.harting.com/66670090347

Identification

Category	Hoods/Housings
Series of hoods/housings	D-Sub InduCom
Type of hood/housing	Shell housing
Description of hood/housing	Suitable for circuit boards

Version

Size	D-Sub 1
Version	Top entry
Cable entry	2x
Strain relief	An additional InduCom cable clamp or a crimp flange - ferrule combination is available dependant on the use of the cable.
Locking type	Hexagonal screw Thread M3
2 parts	Yes
Separable	Yes

Technical characteristics

Tightening torque	0.4 Nm cover screw 0.4 Nm Locking screw
Ambient temperature	-20 ... +90 °C
Degree of protection acc. to IEC 60529	IP30

Material properties

Material (hood/housing)	Zinc die-cast
Material (screw)	Brass, nickel plated



Pushing Performance
Since 1945

Material properties

Length	61.7 mm
Width	31 mm
Height	14.8 mm
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained

Commercial data

Packaging size	10
Net weight	5 g
Country of origin	China
European customs tariff number	85389099
GTIN	5713140163942
ETIM	EC001133
eCl@ss	27440213 D-Sub hood